

Package ‘s2dverification’

October 20, 2015

Type Package

Title Set of Common Tools for Forecast Verification

Version 2.4.5

Date 2015-10-19

Author Virginie Guemas <virginie.guemas@ic3.cat>, Nicolau Manubens Gil <nicolau.manubens@ic3.cat>, Louis-Philippe Caron <louis-philippe.caron@ic3.cat>, Verónica Torralba <veronica.torralba@ic3.cat>, Isabel Andreu-Burillo <isabel.andreu-burillo@ic3.cat>, Fabian Lienert <fabian.lienert@ic3.cat>, Javier Garcia-Serrano <jgarcia@ic3.cat>, Ludovic Auger <ludovic.auger@meteo.fr>, Chloé Prodhomme <chloe.prodhomme@ic3.cat>, Martin Ménéguez <martin.menego@ic3.cat>

Maintainer Nicolau Manubens <nicolau.manubens@ic3.cat>

Description Set of tools to verify forecasts through the computation of typical prediction scores against one or more observational datasets or reanalyses (a reanalysis being a physical extrapolation of observations that relies on the equations from a model, not a pure observational dataset). Intended for seasonal to decadal climate forecasts although can be useful to verify other kinds of forecasts. The package can be helpful in climate sciences for other purposes than forecasting.

License GPL-3

Depends R (>= 2.14.1), methods, maps

Imports ncdf4, GEOMap, geomapdata, mapproj, abind, parallel, bigmemory, SpecsVerification, plyr

LazyData yes

SystemRequirements ls, rm, nco, cdo

Encoding UTF-8

NeedsCompilation no

R topics documented:

s2dverification-package	3
.LoadDataFile	3
ACC	6
Alpha	8

Ano	9
Ano_CrossValid	10
Clim	11
ColorBar	12
ConfigAddVar	13
ConfigApplyMatchingEntries	14
ConfigEditDefinition	16
ConfigEditEntry	17
ConfigFileOpen	19
ConfigMatchingVars	23
ConfigShowSimilarEntries	24
ConfigShowTable	26
Consist_Trend	27
Corr	29
CRPS	30
Enlarge	31
Eno	32
EnoNew	33
Filter	34
FitAcfCoef	35
FitAutocor	36
GenSeries	37
Histo2Hindcast	37
IniListDims	39
InsertDim	40
LeapYear	40
Load	41
Mean1Dim	51
MeanListDim	52
Plot2VarsVsLTime	52
PlotACC	54
PlotAno	55
PlotClim	57
PlotEquiMap	58
PlotSection	60
PlotStereoMap	61
PlotVsLTime	62
ProbBins	63
RatioRMS	65
RatioSDRMS	66
Regression	67
RMS	69
RMSSS	70
sampleDepthData	71
sampleMap	72
sampleTimeSeries	74
Season	75
SelIndices	76
Smoothing	77
Spectrum	78
Spread	79
Trend	80

Index**82**

s2dverification-package*Prediction Model Score*

Description

This package contains a set of tools to score prediction models by comparing experimental data with observational data.

Details

Package: s2dverification
Type: Package
Version: 2.4.5
Date: 2015-10-19
License: GPLv3

First, data has to be loaded from the repository with the function `Load()`. It is needed to specify a variable to load, names for the experimental and observational datasets to load the data from and the starting dates, among other arguments. This will automatically provide two matrices with the observational and experimental data. From then on you can compute the anomalies, climatologies, etc.

Author(s)

Virginie Guemas <virginie.guemas at ic3.cat>
Nicolau Manubens Gil <nicolau.manubens at ic3.cat>
Louis-Philippe Caron <louis-philippe.caron@ic3.cat>
Verónica Torralba <veronica.torralba@ic3.cat>
Fabian Lienert <fabian.lienert at ic3.cat>
Javier Garcia-Serrano <jgarcia at ic3.cat>
Luis Rodrigues <lrodrigues at ic3.cat>
Ludovic Auger <ludovic.auger@meteo.fr>
Chloé Prodhomme <chloe.prodhomme at ic3.cat>
Martin Ménégos <martin.menego at ic3.cat>
Isabel Andreu-Burillo <isabel.andreu-burillo at ic3.cat>

References

Please, for more information load the package and check the help for each function or the documentation attached to the package.

.LoadDataFile

Load Data From File Into Environment

Description

This function receives a 'work piece', a named list which contains information on a data file to be loaded.

It can be run in 'explore' mode or in 'load' mode.

When running in 'explore' mode, the metadata of the file is read and the sizes of the dimensions in the file are returned in a named list:

- 'nmemb': Number of members
- 'nltme': Number of lead-times
- 'lon': Longitudes in the file
- 'lat': Latitudes in the file

When running in 'load' mode it loads and performs any requested computations in additional parameters in the 'work piece', such as interpolating, slicing, ..., and finally stores it in a shared memory matrix pointed by the parameter 'out_pointer' in the 'work piece'.

Usage

```
.LoadDataFile(work_piece, explore_dims = FALSE, silent = FALSE)
```

Arguments

- | | |
|------------|---|
| work_piece | <p>Named list with information on the file to load or explore and additional parameters.</p> <p>The needed variables in the work piece are:</p> <ul style="list-style-type: none"> • In explore mode: <ul style="list-style-type: none"> – dataset_type: 'exp'/'obs' – filename: full path to the data file – dimnames: named list with names 'longitudes', 'latitudes' and 'members' and with values the associated actual dimension names inside the NetCDF files. – namevar: name of the variable in the nc file – is_2d_var: TRUE/FALSE – grid: common grid into which interpolate or NULL if no interpolation – remap: interpolation method ('remapbil'/'remapdis'/'remapcon'/'remapbic') – lon_limits: c(lon_min, lon_max) – lat_limits: c(lat_min, lat_max) – is_file_per_member: TRUE/FALSE • In load mode: <ul style="list-style-type: none"> – dataset_type: 'exp'/'obs' – filename: full path to the data file – dimnames: named list with names 'longitudes', 'latitudes' and 'members' and with values the associated actual dimension names inside the NetCDF files. |
|------------|---|


```
namevar = 'tos', is_2d_var = TRUE, lon_limits = c(-12, 40),
lat_limits = c(27, 48), is_file_per_member = FALSE,
dimnames = list(longitudes = 'longitude', latitudes = 'latitude',
members = 'ensemble')), explore_dims = TRUE, silent = FALSE)
```

ACC

Computes Anomaly Correlation Coefficient (Spatial Correlation)

Description

Matrix `var_exp` & `var_obs` should have dimensions (nexp/nobs, nsdates, nltimes, nlat, nlon) or (nexp/nobs, nsdates, nmember, nltimes, nlat, nlon).

ACC computes the Anomaly Correlation Coefficient for the ensemble mean of each jexp in 1:nexp and each jobs in 1:nobs which gives nexp x nobs ACC for each startdate and each leadtime.

A domain can be selected by providing the list of longitudes/latitudes (lon/lat) of the grid together with the corner of the domain:

```
lonlatbox = c(lonmin, lonmax, latmin, latmax)
```

Usage

```
ACC(var_exp, var_obs, lon = NULL, lat = NULL, lonlatbox = NULL, conf = TRUE,
    conftype = "parametric")
```

Arguments

<code>var_exp</code>	Matrix of experimental anomalies with dimensions: c(nexp, nsdates, nltimes, nlat, nlon) or c(nexp, nsdates, nmembers, nltimes, nlat, nlon)
<code>var_obs</code>	Matrix of observational anomalies, same dimensions as <code>var_exp</code> except along the first dimension and the second if it corresponds to the member dimension.
<code>lon</code>	Array of longitudes of the <code>var_exp</code> / <code>var_obs</code> grids, optional.
<code>lat</code>	Array of latitudes of the <code>var_exp</code> / <code>var_obs</code> grids, optional.
<code>lonlatbox</code>	Domain to select : c(lonmin, lonmax, latmin, latmax), optional.
<code>conf</code>	TRUE/FALSE: confidence intervals or significance level provided or not.
<code>conftype</code>	"parametric" provides a confidence interval for the ACC computed by a Fisher transformation and a significance level for the ACC from a one-sided student-T distribution. "bootstrap" provides a confidence interval for the ACC and MACC computed from bootstrapping on the members with 100 drawings with replacement. To guarantee the statistical robustness of the result, make sure that your experiments/observations/startdates/leadtimes always have the same number of members.

Value

ACC	<p>If conf set as TRUE, Matrix with dimensions: <code>c(nexp, nobs, nsdates, nleadtimes, 4)</code> The fifth dimension of length 4 corresponds to the lower limit of the 95% confidence interval, the ACC, the upper limit of the 95% confidence interval and the 95% significance level. If conf set as FALSE, Anomaly Correlation Coefficient with dimensions: <code>c(nexp, nobs, nsdates, nleadtimes)</code>.</p>
MACC	<p>Mean Anomaly Correlation Coefficient with dimensions: <code>c(nexp, nobs, nleadtimes)</code></p>

Author(s)

History:

- 0.1 - 2013-08 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code
- 1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN
- 1.1 - 2013-09 (C. Prodhomme, <chloe.prodhomme at ic3.cat>) - optimization
- 1.2 - 2014-08 (V. Guemas, <virginie.guemas at ic3.cat>) - Bug-fixes : handling of NA & selection of domain + Simplification of code
- 1.3.0 - 2014-08 (V. Guemas, <virginie.guemas at ic3.cat>) - Booststrapping over members
- 1.3.1 - 2014-09 (C. Prodhomme, <chloe.prodhomme at ic3.cat>) - Add comments and minor style changes
- 1.3.2 - 2015-02 (N. Manubens, <nicolau.manubens at ic3.cat>) - Fixed ACC documentation and examples

Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_$VAR_NAME$_$YEAR$_$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
  leadtimemin = 1, leadtimax = 4, output = 'lonlat',
  latmin = 27, latmax = 48, lonmin = -12, lonmax = 40,
```

```

configfile = configfile)

## End(Not run)

sampleData$mod <- Season(sampleData$mod, 4, 11, 12, 2)
sampleData$obs <- Season(sampleData$obs, 4, 11, 12, 2)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
acc <- ACC(Mean1Dim(ano_exp, 2), Mean1Dim(ano_obs, 2))
PlotACC(acc$ACC, startDates)

```

Alpha

Estimates AutoCorrelation At Lag 1 following Guemas et al, BAMS, 2013b

Description

This function, relying on the `FitAcfCoef()` function, estimates the autocorrelation at lag 1 of the `xdata` array following the method described in Guemas V., Auger L., Doblas-Reyes F., JAMC, 2013. After applying a linear detrending and/or a filtering of any frequency peak if requested, the sample autocorrelation is estimated.

Then the theoretical autocorrelation of an AR1 is fitted to the sample autocorrelation using the Cardano's formula (see `FitAcfCoef()`) to obtain the autocorrelation at lag 1. This method assumes `xdata` is an AR1 process.

Usage

```
Alpha(xdata, detrend = FALSE, filter = FALSE)
```

Arguments

<code>xdata</code>	Timeseries from which the autocorrelation at lag 1 is requested.
<code>detrend</code>	TRUE applies a linear detrending to <code>xdata</code> prior to the estimation of the autocorrelation at lag 1.
<code>filter</code>	TRUE applies a filtering of any frequency peak prior to the estimation of the autocorrelation at lag 1.

Value

Autocorrelation at lag 1

Author(s)

History:

0.1 - 2012-06 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

Examples

```

# Load sample data as in Load() example:
example(Load)
alpha <- Alpha(sampleData$mod[1, 1, , 1])
print(alpha)

```

Ano

Computes Forecast or Observed Anomalies

Description

This function computes anomalies from any experimental or observational matrix output from `Load()` and their climatologies output from `Clim()`.

Usage

```
Ano(var, clim)
```

Arguments

<code>var</code>	Model or observational data: <code>c(nmod/nexp/nobs, nmemb/nparam, nsdates, nlttime)</code> up to <code>c(nmod/nexp/nobs, nmemb/nparam, nsdates, nlttime, nlevel, nlat, nlon)</code>
<code>clim</code>	Climatologies from <code>clim</code> : <code>c(nmod/nexp/nobs, nlttime)</code> up to <code>c(nmod/nexp/nobs, nlttime, nlevel, nlat, nlon)</code> or <code>c(nmod/nexp/nobs, nmemb/nparam, nlttime)</code> up to <code>c(nmod/nexp/nobs, nmemb/nparam, nlttime, nlevel, nlat, nlon)</code> or <code>c(nmod/nexp/nobs, nmemb/nparam, nsdates, nlttime)</code> up to <code>c(nmod/nexp/nobs, nmemb/nparam, nsdates, nlttime, nlevel, nlat, nlon)</code> depending on the options provided to <code>Clim()</code>

Value

Array with same dimensions as 'var'.

Author(s)

History:

0.1 - 2012-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

Examples

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_nb_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_nb_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_nb_months, dim_to_smooth)
PlotAno(smooth_ano_exp, smooth_ano_obs, startDates,
        toptitle = paste('smoothed anomalies'), ytitle = c('K', 'K', 'K'),
        legends = 'ERSST', biglab = FALSE, fileout = 'tos_ano.eps')
```

Ano_CrossValid

Computes Anomalies In Cross-Validation Mode

Description

This function computes anomalies from experimental and observational matrices output from `load()` by subtracting the climatologies computed in a cross-validation mode and with a per-pair method.

Usage

```
Ano_CrossValid(var_exp, var_obs, memb = TRUE)
```

Arguments

<code>var_exp</code>	Model data: c(nmod/nexp, nmemb/nparam, nsdates, nlttime) up to c(nmod/nexp, nmemb/nparam, nsdates, nlttime, nlevel, nlat, nlon)
<code>var_obs</code>	Observational data: c(nobs, nmemb, nsdates, nlttime) up to c(nobs, nmemb, nsdates, nlttime, nlevel, nlat, nlon)
<code>memb</code>	memb: TRUE/FALSE (1 climatology for each member/1 climatology averaging all the members). Default = TRUE.

Value

<code>\$ano_exp</code>	Matrix with same dimensions as <code>var_exp</code>
<code>\$ano_obs</code>	Matrix with same dimensions as <code>var_obs</code>

Author(s)

History:

0.1 - 2011-12 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

Examples

```
# Load sample data as in Load() example:
example(Load)
anomalies <- Ano_CrossValid(sampleData$mod, sampleData$obs)
PlotAno(anomalies$ano_exp, anomalies$ano_obs, startDates,
        toptitle = paste('anomalies'), ytitle = c('K', 'K', 'K'),
        legends = 'ERSST', biglab = FALSE, fileout = 'tos_ano_crossvalid.eps')
```

Clim

*Computes Per-pair/Kharin/Fuckar Climatologies***Description**

This function computes climatologies from the experimental and observational matrices output from `Load()` using one of the following methods:

- 1) per-pair method (Garcia-Serrano and Doblas-Reyes, CD, 2012)
- 2) Kharin method (Karin et al, GRL, 2012)
- 3) Fuckar method (Fuckar et al, GRL, 2014)

`Clim` function computes climatologies using the startdates covered by the whole experiments/observational data sets. The startdates not available for all the data (model and obs) are excluded when computing the climatologies.

Usage

```
Clim(var_exp, var_obs, memb = TRUE, kharin = FALSE, NDV = FALSE)
```

Arguments

<code>var_exp</code>	Model data: <code>c(nmod/nexp, nmemb/nparam, nsdates, ntime)</code> up to <code>c(nmod/nexp, nmemb/nparam, nsdates, ntime, nlevel, nlat, nlon)</code>
<code>var_obs</code>	Observational data: <code>c(nobs, nmemb, nsdates, ntime)</code> up to <code>c(nobs, nmemb, nsdates, ntime, nlevel, nlat, nlon)</code>
<code>memb</code>	<code>memb</code> : TRUE/FALSE (1 climatology for each member). Default = TRUE.
<code>kharin</code>	TRUE/FALSE (if Kharin method is applied or not). Default = FALSE.
<code>NDV</code>	TRUE/FALSE (if Fuckar method is applied or not). Default = FALSE.

Value

<code>clim_exp</code>	Array with same dimensions as <code>var_exp</code> except the third (starting dates) and, depending on the parameters, the second (members), which disappear.
<code>clim_obs</code>	Array with same dimensions as <code>var_obs</code> except the third (starting dates) and, depending on the parameters, the second (members), which disappear.

Author(s)

History:

0.9 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

Examples

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
PlotClim(clim$clim_exp, clim$clim_obs,
         toptitle = paste('sea surface temperature climatologies'),
         ytitle = 'K', monini = 11, listexp = c('CMIP5 IC3'),
         listobs = c('ERSST'), biglab = FALSE, fileout = 'tos_clim.eps')
```

ColorBar

Draws Color Bar

Description

Creates a horizontal or vertical colorbar to introduce in multipanels.

Usage

```
ColorBar(brks, cols = NULL, vert = TRUE, subsampleg = 1, cex = 1)
```

Arguments

brks	Levels.
cols	List of colours, optional.
vert	TRUE/FALSE for vertical/horizontal colorbar.
subsampleg	Supsampling factor of the interval between ticks on the colorbar. Default: 1 = every level
cex	Multiplicative factor to increase the ticks size, optional.

Author(s)

History:

0.1 - 2012-04 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code
 0.2 - 2013-04 (I. Andreu-Burillo, <isabel.andreu-burillo at ic3.cat>) - Vert option
 1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN
 1.1 - 2013-09 (C. Prodhomme <chloe.prodhomme at ic3.cat>) - Add cex option

Examples

```
cols <- c("dodgerblue4", "dodgerblue1", "forestgreen", "yellowgreen", "white",
         "white", "yellow", "orange", "red", "saddlebrown")
lims <- seq(-1, 1, 0.2)
ColorBar(lims, cols)
```

Description

These functions add or remove supported variables to or from the lists of supported 2d or global-mean variables.

Usage

```
ConfigAddVar(configuration, var_type, var_entry)
ConfigRemoveVar(configuration, var_type, var_entry)
```

Arguments

configuration	Configuration object obtained from ConfigFileOpen() or ConfigFileCreate() that contains the lists of variables that will be extended.
var_type	Name of the list of variables to modify. Can take values '2d' if willing to modify the two-dimensional variable list, or 'mean' if willing to modify global mean variable list.
var_entry	Name of the variable to add or remove (can be a regular expression to match sets of variables. See ?ConfigFileOpen).

Value

A modified configuration object is returned.

Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

See Also

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

Examples

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment",
                                "ExampleVariable", "/path/to/ExampleExperiment",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
```

```

# Add another entry
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit second entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 2, var_name = ".*",
                                file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Remove first entry
configuration <- ConfigRemoveEntry(configuration, "experiments",
                                   "file-per-startdate", "ExampleExperiment", "ExampleVariable")
# Show results
ConfigShowTable(configuration, "experiments", "file-per-ensemble")
# Now put variable in list of supported variables. In this example will be a
# two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "ExampleMistake")
# Look in list of variables and see there's nothing similar to what we look
# for. The previous introduction was mistaken
configuration <- ConfigShowSimilarVars(configuration, "Variable")
# Remove variable and add the desired one
configuration <- ConfigRemoveVar(configuration, "2d", "ExampleMistake")
configuration <- ConfigAddVar(configuration, "2d", "ExampleVariable")
# See results
ConfigShowVars(configuration)
# Save the configuration
ConfigFileSave(configuration, config_file, confirm = FALSE)

```

ConfigApplyMatchingEntries

Apply Matching Entries To Dataset Name And Variable Name To Find Related Info

Description

Given a pair of dataset name and variable name, this function determines, by reading the configuration lists and tables, what kind of dataset it is and in what format it is stored (file-per-dataset, file-per-member, ...). Then it applies all the matching entries found in the corresponding configuration table to work out the dataset main path, file path, actual name of variable inside NetCDF files, ...

Usage

```
ConfigApplyMatchingEntries(configuration, var, exp = NULL, obs = NULL,
                           show_entries = FALSE, show_result = TRUE)
```

Arguments

configuration	Configuration object obtained from ConfigFileOpen() or ConfigFileCreate().
var	Name of the variable to load. Will be interpreted as a string, regular expressions do not apply here. Examples: 'tas' or 'tasmax_q90'.

exp	Set of experimental dataset identifiers. Will be interpreted as a strings, regular expressions do not apply here. Can be NULL (not to check in experimental dataset tables), and takes by default NULL. Examples: c('EnsEcmwfSeas', 'EnsUkmoSeas'), c('i00k').
obs	Set of observational dataset identifiers. Will be interpreted as a strings, regular expressions do not apply here. Can be NULL (not to check in observational dataset tables), and takes by default NULL. Examples: c('GLORYS', 'ERAint'), c('NCEP').
show_entries	Flag to stipulate whether to show the found matching entries for all datasets and variable name.
show_result	Flag to stipulate whether to show the result of applying all the matching entries (dataset main path, file path, ...).

Value

A modified configuration object is returned.

Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

See Also

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

Examples

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment2" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 1, var_name = ".*",
                                file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Now put variable in list of supported variables. In this example will be a
# two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "ExampleVariable")
# Change the default grid
configuration <- ConfigEditDefinition(configuration, "DEFAULT_GRID",
                                      "r256x128", confirm = FALSE)
# Now apply matching entries for variable and experiment name and show the
```

```
# result
match_info <- ConfigApplyMatchingEntries(configuration, 'tas',
                                         exp = c('ExampleExperiment2'), show_result = TRUE)
```

ConfigEditDefinition

Add Modify Or Remove Variable Definitions In Configuration

Description

These functions help in adding, modifying or removing variable definitions in a configuration object obtained with ConfigFileOpen() or ConfigFileCreate().

ConfigEditDefinition() will add the definition if not existing.

Usage

```
ConfigEditDefinition(configuration, name, value, confirm = TRUE)
ConfigRemoveDefinition(configuration, name)
```

Arguments

configuration	Configuration object obtained with ConfigFileOpen() or ConfigFileCreate().
name	Name of the variable to add/modify/remove.
value	Value to associate to the variable.
confirm	Flag to stipulate whether to ask for confirmation if the variable is being modified. Takes by default TRUE.

Value

A modified configuration object is returned.

Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

See Also

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

Examples

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment2" and variable
# "ExampleVariable" to some information about its location.
```



```

configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 1, var_name = ".*",
                                file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Now put variable in list of supported variables. In this example will be a
# two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "ExampleVariable")
# Change the default grid
configuration <- ConfigEditDefinition(configuration, "DEFAULT_GRID",
                                      "r256x128", confirm = FALSE)
# Now apply matching entries for variable and experiment name and show the
# result
match_info <- ConfigApplyMatchingEntries(configuration, 'tas',
                                          exp = c('ExampleExperiment2'), show_result = TRUE)

```

ConfigEditEntry	<i>Add, Remove Or Edit Entries In The Configuration</i>
-----------------	---

Description

ConfigAddEntry(), ConfigEditEntry() and ConfigRemoveEntry() are functions to manage entries in a configuration object created with ConfigFileOpen().

Before adding an entry, make sure the defaults don't do already what you want (ConfigShowDefinitions(), ConfigShowTable()).

Before adding an entry, make sure it doesn't override and spoil what other entries do (ConfigShowTable(), ConfigFileOpen()).

Before adding an entry, make sure there aren't other entries that already do what you want (ConfigShowSimilarEntries()).

Usage

```

ConfigAddEntry(configuration, dataset_type, store_format, position = "last",
               dataset_name = ".*", var_name = ".*", main_path = ".*",
               file_path = ".*", nc_var_name = ".*", grid = ".*", suffix = ".*",
               varmin = ".*", varmax = ".*")
ConfigEditEntry(configuration, dataset_type, store_format, position,
               dataset_name = NULL, var_name = NULL, main_path = NULL,
               file_path = NULL, nc_var_name = NULL, grid = NULL,
               suffix = NULL, varmin = NULL, varmax = NULL)
ConfigRemoveEntry(configuration, dataset_type, store_format,
                  dataset_name = NULL, var_name = NULL, position = NULL)

```

Arguments

configuration

Configuration object obtained via ConfigFileOpen() or ConfigFileCreate() that will be modified accordingly.

`dataset_type` Whether to modify a table of experimental datasets or a table of observational datasets. Can take values 'experiments' or 'observations' respectively.

`store_format` There's a table associated to each storage format (see ?ConfigFileOpen). 'store_format' tells which one to load. Can take values 'file-per-startdate', 'file-per-member' (if 'dataset_type' is 'experiments'), or 'file-per-member', 'file-per-month', 'file-per-dataset' (if 'dataset_type' is 'observations').

`position` 'position' tells the index in the table of the entry to edit or remove. Use ConfigShowTable() to see the index of the entry. In ConfigAddEntry() it can also take the value "last" (default), that will put the entry at the end of the corresponding level, or "first" at the beginning. See ?ConfigFileOpen for more information. If 'dataset_name' and 'var_name' are specified this argument is ignored in ConfigRemoveEntry().

`dataset_name, var_name, main_path, file_path, nc_var_name, grid, suffix, varmin, varmax` These parameters tell the dataset name, variable name, main path, ..., of the entry to add, edit or remove. 'dataset_name' and 'var_name' can take as a value a POSIX 1003.2 regular expression (see ?ConfigFileOpen). Other parameters can take as a value a shell globbing expression (see ?ConfigFileOpen). 'dataset_name' and 'var_name' take by default the regular expression '.*' (match any dataset and variable name), and the others take by default '*' (associate to the pair 'dataset_name' and 'var_name' all the defined default values. In this case '*' has a special behaviour, it won't be used as a shell globbing expression. See ?ConfigFileOpen and ?ConfigShowDefinitions). 'var_min' and 'var_max' must be a character string. To define these values, you can use defined variables via \$VARIABLE_NAME\$ or other entry attributes via \$ATTRIBUTE_NAME\$. See ?ConfigFileOpen for more information.

Value

The function returns an accordingly modified configuration object. To apply the changes in the configuration file it must be saved using ConfigFileSave().

Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

See Also

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

Examples

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
```

```

# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment",
                                "ExampleVariable", "/path/to/ExampleExperiment",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")

# Add another entry
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")

# Edit second entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 2, var_name = ".*",
                                file_path = "$VAR_NAME$/${VAR_NAME}_${START_DATE$.nc}")

# Remove first entry
configuration <- ConfigRemoveEntry(configuration, "experiments",
                                   "file-per-startdate", "ExampleExperiment", "ExampleVariable")

# Show results
ConfigShowTable(configuration, "experiments", "file-per-ensemble")
# Now put variable in list of supported variables. In this example will be a
# two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "ExampleMistake")
# Look in list of variables and see there's nothing similar to what we look
# for. The previous introduction was mistaken
configuration <- ConfigShowSimilarVars(configuration, "Variable")
# Remove variable and add the desired one
configuration <- ConfigRemoveVar(configuration, "2d", "ExampleMistake")
configuration <- ConfigAddVar(configuration, "2d", "ExampleVariable")
# See results
ConfigShowVars(configuration)
# Save the configuration
ConfigFileSave(configuration, config_file, confirm = FALSE)

```

ConfigFileOpen

*Functions To Create Open And Save Configuration File***Description**

These functions help in creating, opening and saving configuration files.

Usage

```

ConfigFileOpen(file_path, silent = FALSE)
ConfigFileCreate(file_path, confirm = TRUE)
ConfigFileSave(configuration, file_path, confirm = TRUE)

```

Arguments

file_path	Path to the configuration file to create/open/save.
silent	Flag to activate or deactivate verbose mode. Defaults to FALSE (verbose mode on).

configuration	Configuration object to save in a file.
confirm	Flag to stipulate whether to ask for confirmation when saving a configuration file that already exists. Defaults to TRUE (confirmation asked).

Details

ConfigFileOpen() loads all the data contained in the configuration file specified as parameter 'file_path'. Returns a configuration object with the variables needed for the configuration file mechanism to work.

This function is called from inside the Load() function to load the configuration file specified in 'configfile'.

ConfigFileCreate() creates an empty configuration file and saves it to the specified path. It may be opened later with ConfigFileOpen() to be edited. Some default values are set when creating a file with this function, you can check these with ConfigShowDefinitions().

ConfigFileSave() saves a configuration object into a file, which may then be used from Load().

Two examples of configuration files can be found inside the 'inst/config/' folder in the package:

- BSC.conf: configuration file used at BSC-CNS. Contains location data on several datasets and variables.
- template.conf: very simple configuration file intended to be used as pattern when starting from scratch.

How the configuration file works:

~~~~~

It contains two lists and five tables.

Each of these have a header that starts with '!!'. These are key lines and should not be removed or reordered.

Lines starting with '#' and blank lines will be ignored.

The first list should contain all the supported 2-dimensional variables.

The second list should contain all the supported global mean variables.

Regular expressions[1] can be used in these lists to match more than one variable name.

The first table contains information about experiments (which are stored in a file per ensemble per starting date format).

The second table contains information about file-per-member experiments (which are stored in a file per member per starting date format).

The third table contains information about observations (which are stored in a file per month per ensemble format).

The fourth table contains information about the file-per-member observations (which are stored in a file per month per member format).

The fifth table contains information about the file-per-dataset observations (which contain all the dataset values in a single file).

Each table entry is a list of comma-separated elements.

The two first are part of a key that is associated to a value formed by the other elements.

The key elements are a dataset identifier and a variable name.

The value elements are the dataset main path, dataset file path, grid (unless it is an observation table entry), the variable name inside the .nc file, a default suffix (explained below) and a minimum and maximum values beyond which loaded data is deactivated.

Given a dataset name and a variable name, a full path is obtained concatenating the main path and the file path with a slash (/) in between.

Also the grid (in the case it is an experiment), the nc variable name, the suffixes and the limit values are obtained.

Any of the elements in the keys can contain regular expressions that will cause matching for sets of dataset names or variable names.

The dataset path and file path can contain shell globbing expressions[2] that will cause matching for sets of paths when fetching the file in the full path.

The full path can point to an OPeNDAP URL.

Any of the elements in the value can contain variables that will be replaced to an associated string. Variables can be defined only immediately above any of the tables header.

The pattern of a variable definition is

VARIABLE\_NAME = VARIABLE\_VALUE

and can be accessed from within the table values or from within the variable values as

\$VARIABLE\_NAMES

For example:

FILE\_NAME = tos.nc

!!table of experiments

ecmwf, tos, /path/to/dataset, \$FILE\_NAME\$

There are some reserved variables that will offer information about the store frequency, the current startdate Load() is fetching, etc:

\$START\_DATE\$, \$STORE\_FREQ\$

for file-per-member datasets: \$MEMBER\_NUMBER\$

for observations: \$YEAR\$, \$MONTH\$, \$DAY\$

Additionally, from an element in an entry value you can access the other elements of the entry as:

\$EXP\_NAMES\$, \$VAR\_NAMES\$, \$EXP\_MAIN\_PATH\$, \$EXP\_FILE\_PATH\$, \$GRID\$,

\$VAR\_NAMES\$, \$SUFFIX\$, \$VAR\_MIN\$, \$VAR\_MAX\$

and in an observation as:

\$OBS\_NAMES\$, \$VAR\_NAMES\$, \$OBS\_MAIN\_PATH\$, \$OBS\_FILE\_PATH\$, \$VAR\_NAMES\$,

\$SUFFIX\$, \$VAR\_MIN\$, \$VAR\_MAX\$

The variable \$SUFFIX\$ is useful because it can be used to take part in the main or file path. For example: '/path/to/\$SUFFIX\$/dataset'.

It will be replaced by the value in the column that corresponds to the suffix unless the user specifies a different suffix via the parameter 'suffixexp' or 'suffixobs'.

This way the user is able to load two variables with the same name in the same dataset but with slight modifications, with a suffix anywhere in the path to the data that advises of this slight modification.

The entries in a table will be grouped in 4 levels of specificity:

1. General entries:
  - the key dataset name and variable name are both a regular expression matching any sequence of characters (.\* ) that will cause matching for any pair of dataset and variable names
  - Example: .\*, .\*, /dataset/main/path, file/path, grid, nc\_var\_name, suffix, var\_min, var\_max
2. Dataset entries:
  - the key variable name matches any sequence of characters
  - Example: ecmwf, .\*, /dataset/main/path, file/path, grid, nc\_var\_name, suffix, var\_min, var\_max
3. Variable entries:
  - the key dataset name matches any sequence of characters
  - Example: .\*, tos, /dataset/main/path, file/path, grid, nc\_var\_name, suffix, var\_min, var\_max
4. Specific entries:
  - both key values are specified
  - Example: ecmwf, tos, /dataset/main/path, file/path, grid, nc\_var\_name, suffix, var\_min, var\_max

Given a pair of dataset name and variable name for which we want to know the full path, all the rules that match will be applied from more general to more specific.

If there is more than one entry per group that match a given key pair, these will be applied in the order of appearance in the configuration file (top to bottom).

An asterisk (\*) in any value element will be interpreted as 'leave it as is or take the default value if yet not defined'.

The default values are defined in the following reserved variables:

```
$DEFAULT_EXP_MAIN_PATH$, $DEFAULT_EXP_FILE_PATH$, $DEFAULT_GRID$, $DE-
FAULT_NC_VAR_NAMES$, $DEFAULT_OBS_MAIN_PATH$, $DEFAULT_OBS_FILE_PATH$,
$DEFAULT_SUFFIX$, $DEFAULT_VAR_MIN$, $DEFAULT_VAR_MAX$,
$DEFAULT_DIM_NAME_LATITUDE$, $DEFAULT_DIM_NAME_LONGITUDE$, $DEFAULT_DIM_NAME_M
```

Trailing asterisks in an entry are not mandatory. For example

```
ecmwf, .*, /dataset/main/path, *, *, *, *, *, *
```

will have the same effect as

```
ecmwf, .*, /dataset/main/path
```

A double quote only (") in any key or value element will be interpreted as 'fill in with the same value as the entry above'.

The pattern to obtain the full path by concatenating the dataset main path and the dataset file path can be adjusted in the variables EXP\_FULL\_PATH and OBS\_FULL\_PATH, which are defined by default as

```
EXP_FULL_PATH = $EXP_MAIN_PATH$/$EXP_FILE_PATH$
```

```
OBS_FULL_PATH = $OBS_MAIN_PATH$/$OBS_FILE_PATH$
```

## Value

ConfigFileOpen() returns a configuration object with all the information for the configuration file mechanism to work.

ConfigFileSave() returns TRUE if the file has been saved and FALSE otherwise.

ConfigFileCreate() returns nothing.

## Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

## References

[1] <https://stat.ethz.ch/R-manual/R-devel/library/base/html/regex.html>

[2] <http://tldp.org/LDP/abs/html/globberref.html>

## See Also

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

## Examples

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
```

```

configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment2" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 1, var_name = ".*",
                                file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Now put variable in list of supported variables. In this example will be a
# two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "ExampleVariable")
# Change the default grid
configuration <- ConfigEditDefinition(configuration, "DEFAULT_GRID", "r256x128",
                                     confirm = FALSE)
# Now apply matching entries for variable and experiment name and show the
# result
match_info <- ConfigApplyMatchingEntries(configuration, 'tas',
                                          exp = c('ExampleExperiment2'), show_result = TRUE)
# Finally save the configuration file.
ConfigFileSave(configuration, config_file, confirm = FALSE)

```

---

ConfigMatchingVars *Find Entries In List Of Supported Variables That Match A Variable*

---

## Description

Given a specific variable name, this function checks and shows if it matches with any of the patterns in the lists of supported variables.

## Usage

```
ConfigMatchingVars(configuration, var, show = TRUE)
```

## Arguments

|               |                                                                                             |
|---------------|---------------------------------------------------------------------------------------------|
| configuration | Configuration object obtained from ConfigFileCreate() or ConfigFileOpen().                  |
| var           | Variable name which to check if is supported or not.                                        |
| show          | Boolean to stipulate whether to show the matching entries or not.<br>Takes TRUE by default. |

## Value

A boolean is returned. It tells whether the variable is supported as a 2-dimensional variable (TRUE) or as a global mean variable (FALSE).

## Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

**See Also**

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

**Examples**

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment2" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 1, var_name = ".*",
                                file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Now put a pattern to the list of supported variables. In this example will
# be a two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "Example.*Variable")
# Check if some variables are supported after adding this rule
ConfigMatchingVars(configuration, "Example10Variable")
ConfigMatchingVars(configuration, "ExampleSomeVariable")
ConfigMatchingVars(configuration, "ExampleVariable")
```

---

ConfigShowSimilarEntries

*Find Similar Entries In Lists Of Variables And Tables Of Datasets*

---

**Description**

These functions help in finding similar entries in lists of supported variables or in tables of supported datasets by comparing all entries with some given information.

This is useful when dealing with complex configuration files and not sure if already support certain variables or datasets.

At least one field must be provided in ConfigShowSimilarEntries(). Other fields can be unspecified and won't be taken into account. If more than one field is provided, sameness is averaged over all provided fields and entries are sorted from higher average to lower.

**Usage**

```
ConfigShowSimilarEntries(configuration, dataset_name = NULL, var_name = NULL,
                          main_path = NULL, file_path = NULL, nc_var_name = NULL,
                          grid = NULL, suffix = NULL, varmin = NULL,
                          varmax = NULL, n_results = 10)
ConfigShowSimilarVars(configuration, var_name, n_results = 5)
```



**Arguments**

|                            |                                                                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>configuration</code> | Configuration object obtained either from <code>ConfigFileCreate()</code> or <code>ConfigFileOpen()</code> .                                                                     |
| <code>dataset_name</code>  | Optional dataset name to look for similars of.                                                                                                                                   |
| <code>var_name</code>      | Optional variable name to look for similars of.                                                                                                                                  |
| <code>main_path</code>     | Optional main path to look for similars of.                                                                                                                                      |
| <code>file_path</code>     | Optional file path to look for similars of.                                                                                                                                      |
| <code>nc_var_name</code>   | Optional variable name inside NetCDF file to look for similars of.                                                                                                               |
| <code>grid</code>          | Optional grid to look for similars of.                                                                                                                                           |
| <code>suffix</code>        | Optional suffix to look for similars of.                                                                                                                                         |
| <code>varmin</code>        | Optional variable minimum to look for similars of.                                                                                                                               |
| <code>varmax</code>        | Optional variable maximum to look for similars of.                                                                                                                               |
| <code>n_results</code>     | Top ' <code>n_results</code> ' alike results will be shown only.<br>Defaults to 10 in <code>ConfigShowSimilarEntries()</code> and to 5 in <code>ConfigShowSimilarVars()</code> . |

**Details**

Sameness is calculated with string distances as specified by Simon White in [1].

**Value**

These functions return information about the found matches.

**Author(s)**

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

**References**

[1] Simon White, string seamness: <http://www.catalysoft.com/articles/StrikeAMatch.html>

**See Also**

`ConfigAddVar`, `ConfigApplyMatchingEntries`, `ConfigEditDefinition`, `ConfigEditEntry`, `ConfigFileOpen`, `ConfigMatchingVars`, `ConfigShowSimilarEntries`, `ConfigShowTable`

**Examples**

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment2" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
```

```

        "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
    "file-per-startdate", 1, var_name = ".*",
    file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Now put a pattern to the list of supported variables. In this example will
# be a two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "Example.*Variable")
# Look for similar entries
ConfigShowSimilarEntries(configuration, dataset_name = "Exper",
    var_name = "Vari")
ConfigShowSimilarVars(configuration, "Vari")

```

---

|                 |                                                        |
|-----------------|--------------------------------------------------------|
| ConfigShowTable | <i>Show Configuration Tables Lists And Definitions</i> |
|-----------------|--------------------------------------------------------|

---

## Description

These functions show the tables of supported datasets, lists of supported variables and definitions in a configuration object obtained via ConfigFileCreate() or ConfigFileOpen().

## Usage

```

ConfigShowTable(configuration, dataset_type, store_format, line_numbers = NULL)
ConfigShowDefinitions(configuration)
ConfigShowVars(configuration)

```

## Arguments

|               |                                                                                                                                                                                                                                                                                                  |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| configuration | Configuration object obtained from ConfigFileCreate() or ConfigFileOpen().                                                                                                                                                                                                                       |
| dataset_type  | In ConfigShowTable(), 'dataset_type' tells whether the table to show is of experimental datasets or of observational datasets.<br>Can take values 'experiments' or 'observations'.                                                                                                               |
| store_format  | In ConfigShowTable(), 'store_format' tells the store format of the table to show.<br>Can take values 'file-per-startdate', 'file-per-member' if 'dataset_type' is 'experiments'.<br>Can take values 'file-per-month', 'file-per-member', 'file-per-dataset' if 'dataset_type' is 'observations'. |
| line_numbers  | 'line_numbers' is an optional vector of numbers as long as the number of entries in the specified table.<br>Intended for internal use.                                                                                                                                                           |

## Value

These functions return nothing.

## Author(s)

History:

0.1 - 2015-05 (N. Manubens, <nicolau.manubens at ic3.cat>) - First version

**See Also**

ConfigAddVar, ConfigApplyMatchingEntries, ConfigEditDefinition, ConfigEditEntry, ConfigFileOpen, ConfigMatchingVars, ConfigShowSimilarEntries, ConfigShowTable

**Examples**

```
# Create an empty configuration file
config_file <- paste0(tempdir(), "/example.conf")
ConfigFileCreate(config_file, confirm = FALSE)
# Open it into a configuration object
configuration <- ConfigFileOpen(config_file)
# Add an entry at the bottom of 4th level of file-per-startdate experiments
# table which will associate the experiment "ExampleExperiment2" and variable
# "ExampleVariable" to some information about its location.
configuration <- ConfigAddEntry(configuration, "experiments",
                                "file-per-startdate", "last", "ExampleExperiment2",
                                "ExampleVariable", "/path/to/ExampleExperiment2",
                                "ExampleVariable/ExampleVariable_${START_DATE$.nc}")
# Edit entry to generalize for any variable. Changing variable needs .
configuration <- ConfigEditEntry(configuration, "experiments",
                                "file-per-startdate", 1, var_name = ".*",
                                file_path = "$VAR_NAME$/$VAR_NAME_${START_DATE$.nc}")
# Now put a pattern to the list of supported variables.
# In this example will be a two-dimensional variable.
configuration <- ConfigAddVar(configuration, "2d", "Example.*Variable")
# Show tables, lists and definitions
ConfigShowTable(configuration, 'experiments', 'file-per-startdate')
ConfigShowVars(configuration)
ConfigShowDefinitions(configuration)
```

---

Consist\_Trend

---

*Computes Trends Using Only Model Data For Which Observations  
Are Available*


---

**Description**

Computes trends by least square fitting together with the associated error interval for both the observational and model data.

Provides also the detrended observational and modeled data.

The trend is computed along the second dimension, expected to be the start date dimension (the user is supposed to perform an ensemble averaging operation with `Mean1Dim()` prior to using `Consist_trend()`).

**Usage**

```
Consist_Trend(var_exp, var_obs, interval = 1)
```

**Arguments**

`var_exp` Ensemble mean of model hindcasts with dimensions:  
`c(nmod/nexp, nsdates, ntime)` up to  
`c(nmod/nexp, nsdates, ntime, nlevel, nlat, nlon)`

|                       |                                                                                                                                                                                                                                  |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>var_obs</code>  | Ensemble mean of observational data with dimensions:<br><code>c(nobs, nsdates, ntime)</code> up to<br><code>c(nobs, nsdates, ntime, nlevel, nlat, nlon)</code><br>Dimensions 2 to 6 should be the same as <code>var_exp</code> . |
| <code>interval</code> | Number of months/years between 2 start dates. Default = 1. The trends will be provided respectively in field unit per month or per year.                                                                                         |

**Value**

|                             |                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\$trend</code>        | Trends of model and observational data with dimensions:<br><code>c(nmod/nexp + nobs, 3, ntime)</code> up to<br><code>c(nmod/nexp + nobs, 3, ntime, nlevel, nlat, nlon)</code><br>The length 3 dimension corresponds to the lower limit of the 95% confidence interval, the slope of the trends and the upper limit of the 95% confidence interval. |
| <code>\$detrendedmod</code> | Same dimensions as <code>var_exp</code> with linearly detrended values of <code>var_exp</code> along the second = start date dimension.                                                                                                                                                                                                            |
| <code>\$detrendedobs</code> | Same dimensions as <code>var_exp</code> with linearly detrended values of <code>var_obs</code> along the second = start date dimension.                                                                                                                                                                                                            |

**Author(s)****History:**

0.1 - 2011-11 (V. Guemas, &lt;vguemas at ic3.cat&gt;) - Original code

1.0 - 2013-09 (N. Manubens, &lt;nicolau.manubens at ic3.cat&gt;) - Formatting to R CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_months, dim_to_smooth)
dim_to_mean <- 2 # Mean along members
years_between_startdates <- 5
trend <- Consist_Trend(Mean1Dim(smooth_ano_exp, dim_to_mean),
                      Mean1Dim(smooth_ano_obs, dim_to_mean),
                      years_between_startdates)

PlotVsLTime(trend$trend, toptitle = "trend", ytitle = "K/(5 years)",
            monini = 11, limits = c(-0.8, 0.8), listexp = c('CMIP5 IC3'),
            listobs = c('ERSST'), biglab = FALSE, hlines = c(0),
            fileout = 'tos_consist_trend.eps')
PlotAno(InsertDim(trend$detrendedmod, 2, 1), InsertDim(trend$detrendedobs, 2, 1),
        startDates, "Detrended tos anomalies", ytitle = 'K',
        legends = 'ERSST', biglab = FALSE, fileout = 'tos_detrended_ano.eps')
```

---

|      |                                                                                    |
|------|------------------------------------------------------------------------------------|
| Corr | <i>Computes Correlation Skill Measure (Temporal Correlation Along Start Dates)</i> |
|------|------------------------------------------------------------------------------------|

---

## Description

Matrix `var_exp` & `var_obs` should have the same dimensions except along `posloop` dimension where the length can be different, with the number of experiments/models for `var_exp` (`nexp`) and the number of obserational datasets for `var_obs` (`nobs`).

Corr computes the correlation skill of each `jexp` in `1:nexp` against each jobs in `1:nobs` which gives `nexp` x `nobs` correlation skill measures for each other grid point of the matrix (each latitude/longitude/level/leadtime).

The correlations are computed along the `poscor` dimension which should correspond to the `startdate` dimension. If `compROW` is given, the correlations are computed only if rows along the `compROW` dimension are complete between `limits[1]` and `limits[2]`, that mean with no NA between `limits[1]` and `limits[2]`. This option can be activated if the user wishes to account only for the forecasts for which observations are available at all leadtimes.

Default: `limits[1] = 1` and `limits[2] = length(compROW dimension)`.

The confidence interval is computed by a Fisher transformation.

The significance level relies on a one-sided student-T distribution.

We can modify the treshold of the test modifying `siglev` (default value=0.95).

## Usage

```
Corr(var_exp, var_obs, posloop = 1, poscor = 2, compROW = NULL, limits = NULL,
      siglev = 0.95, method = 'pearson')
```

## Arguments

|                      |                                                                                                                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>var_exp</code> | Matrix of experimental data.                                                                                                                                                                |
| <code>var_obs</code> | Matrix of observational data, same dimensions as <code>var_exp</code> except along <code>posloop</code> dimension, where the length can be <code>nobs</code> instead of <code>nexp</code> . |
| <code>posloop</code> | Dimension <code>nobs</code> and <code>nexp</code> .                                                                                                                                         |
| <code>poscor</code>  | Dimension along which correlation are to be computed (the dimension of the start dates).                                                                                                    |
| <code>compROW</code> | Data taken into account only if ( <code>compROW</code> )th row is complete.<br>Default = NULL.                                                                                              |
| <code>limits</code>  | Complete between <code>limits[1]</code> & <code>limits[2]</code> . Default = NULL.                                                                                                          |
| <code>siglev</code>  | Significance level according. Default = 0.95.                                                                                                                                               |
| <code>method</code>  | Type of correlation: 'pearson', 'spearman' or 'kendall'. Default='pearson'                                                                                                                  |

## Value

Matrix with dimensions :

`c(length(posloop) in var_exp, length(posloop) in var_obs, 4, all other dimensions of var_exp & var_obs except poscor)`.

The third dimension of length 4 corresponds to the lower limit of the 95% confidence interval, the correlation, the upper limit of the 95% confidence interval and the 95% significance level given by a one-sided T-test.

**Author(s)**

«««<< HEAD History: 0.1 - 2011-04 (V. Guemas, <vguemas at ic3.cat>) - Original code 1.0  
 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN 1.1  
 - 2014-10 (M. Menegoz, <martin.menegoz at ic3.cat>) - Adding siglev argument 1.2 -  
 2015-03 (L.P. Caron, <louis-philippe.caron at ic3.cat>) - Adding method argument  
 ===== History:  
 0.1 - 2011-04 (V. Guemas, <vguemas at ic3.cat>) - Original code  
 1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN  
 1.1 - 2014-10 (M. Menegoz, <martin.menegoz at ic3.cat>) - Adding siglev argument  
 »»»> develop-cran-2.3.2

**Examples**

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_months, dim_to_smooth)
dim_to_mean <- 2 # Mean along members
required_complete_row <- 3 # Discard start dates which contain any NA lead-times
leadtimes_per_startdate <- 60
corr <- Corr(Mean1Dim(smooth_ano_exp, dim_to_mean),
             Mean1Dim(smooth_ano_obs, dim_to_mean),
             compROW = required_complete_row,
             limits = c(ceiling((runmean_months + 1) / 2),
                        leadtimes_per_startdate - floor(runmean_months / 2)))
PlotVsLTime(corr, toptitle = "correlations", ytitle = "correlation",
             monini = 11, limits = c(-1, 2), listexp = c('CMIP5 IC3'),
             listobs = c('ERSST'), biglab = FALSE, hlines = c(-1, 0, 1),
             fileout = 'tos_cor.eps')
```

CRPS

*Compute Continuous Ranked Probability Score (CRPS) For Ensemble Forecasts*

**Description**

Returns the value of the CRPS.

**Usage**

```
CRPS(obs, pred)
```

**Arguments**

|      |                                                                                                                                          |
|------|------------------------------------------------------------------------------------------------------------------------------------------|
| obs  | Vector of observations for a continuous variable (e.g. rainfall)                                                                         |
| pred | Matrix of ensemble forecasts for a continuous variable (e.g. rainfall).<br>It should have the following structure pred[nmembers,nsdates] |

**Value**

CRPS                      Continuous ranked probability score

**Author(s)**

History:

1.0 - 2013-03-12 (L. Rodrigues, <lrodrigues at ic3.cat>) - Original code

1.1 - 2014-11-21 (V. Torralba, <veronica.torralba at ic3.cat>) - Changes in the documentation

**References**

Wilks (2006) Statistical Methods in the Atmospheric Sciences.

Jolliffe and Stephenson (2012) Forecast verification: A practitioner's guide in the Atmospheric science

Hersbach (2000) Weather and Forecasting 15:559-570

**Examples**

```
a <- runif(10)
b <- array(, dim = c(10,10))
for (i in 1:10) {
  b[i, ] <- runif(10)
}
x <- CRPS(a, b)
x$CRPS
```

---

Enlarge

*Extends The Number Of Dimensions of A Matrix*

---

**Description**

Extends the number of dimensions of var to numdims (the added dimensions have length 1).

**Usage**

```
Enlarge(var, numdims)
```

**Arguments**

var                      Matrix to be extended.

numdims                Output number of dimensions.

**Value**

Extended matrix.

**Author(s)**

History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code 1.0 - 2013-09

(N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

## Examples

```
data <- array(1, c(2, 2, 3))
print(dim(Enlarge(data, 5)))
```

Eno

*Computes Effective Sample Size With Classical Method*

## Description

Computes the effective number of independant data along the posdim dimension of a matrix.  
This effective number of independant date may be required to perform statistical/inference tests.  
Based on eno function from Caio Coelho from rclim.txt.

## Usage

```
Eno(obs, posdim)
```

## Arguments

|        |                                                             |
|--------|-------------------------------------------------------------|
| obs    | Matrix of any number of dimensions up to 10.                |
| posdim | Dimension along which to compute the effective sample size. |

## Value

Same dimensions as var but without the posdim dimension.

## Author(s)

History:

0.1 - 2011-05 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

## Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$_$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)
```



```
# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
                  output = 'lonlat', latmin = 27, latmax = 48, lonmin = -12,
                  lonmax = 40, configfile = configfile)

## End(Not run)

sampleData$mod <- Season(sampleData$mod, 4, 11, 1, 12)
eno <- Eno(sampleData$mod[1, 1, , 1, , ], 1)
PlotEquiMap(eno, sampleData$lon, sampleData$lat)
```

EnoNew

*Computes Effective Sample Size Following Guemas et al, BAMS, 2013b*

## Description

This function computes the equivalent number of independent data in the xdata array following the method described in Guemas V., Auger L., Doblas-Reyes F., JAMC, 2013. The method relies on the Trenberth (1984) formula combined with a reduced uncertainty of the estimated autocorrelation function compared to the original approach.

## Usage

```
EnoNew(xdata, detrend = FALSE, filter = FALSE)
```

## Arguments

|         |                                                                                                                      |
|---------|----------------------------------------------------------------------------------------------------------------------|
| xdata   | Timeseries from which the equivalent number of independent data is requested                                         |
| detrend | TRUE applies a linear detrending to xdata prior to the estimation of the equivalent number of independent data.      |
| filter  | TRUE applies a filtering of any frequency peak prior to the estimation of the equivalent number of independent data. |

## Author(s)

History:

0.1 - 2012-06 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
```

```

data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
  leadtimemin = 1, leadtimemax = 4, output = 'lonlat',
  latmin = 27, latmax = 48, lonmin = -12, lonmax = 40,
  configfile = configfile)

## End(Not run)

eno <- EnoNew(sampleData$mod[1, 1, , 1, 2, 3])
print(eno)

```

---

Filter

---

*Filter Frequency Peaks From An Array*


---

## Description

This function filters from the xdata array, the signal of frequency freq.

The filtering is performed by dichotomy, seeking for the frequency around freq and the phase that maximizes the signal to subtract to xdata.

The maximization of the signal to subtract relies on a minimization of the mean square differences between xdata and a cosine of given frequency and phase.

## Usage

```
Filter(xdata, freq)
```

## Arguments

|       |                       |
|-------|-----------------------|
| xdata | Array to be filtered. |
| freq  | Frequency to filter.  |

## Value

Filtered Array

## Author(s)

History:

0.1 - 2012-02 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2012-02 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# Load sample data as in Load() example:
example(Load)
ensmod <- Mean1Dim(sampleData$mod, 2)
for (jstartdate in 1:3) {
  spectrum <- Spectrum(ensmod[1, jstartdate, ])
  for (jlen in 1:dim(spectrum)[1]) {
    if (spectrum[jlen, 2] > spectrum[jlen, 4]) {
      ensmod[1, jstartdate, ] <- Filter(ensmod[1, jstartdate, ],
                                         spectrum[jlen, 1])
    }
  }
}
PlotAcf(InsertDim(ensmod, 2, 1), sdates = startDates, fileout =
        'filtered_ensemble_mean.eps')
```

FitAcfCoef

*Fits an AR1 AutoCorrelation Function Using the Cardano Formula*

## Description

This function finds the minimum point of the fourth order polynom  $(a - x)^2 + 0.25(b - x)^2$  written to fit the two autoregression coefficients  $a$  and  $b$ .

Thanks to the Cardano formula, provided  $a$  and  $b$  in  $[0, 1]$ , the problem is well posed,  $\Delta > 0$  and there is only one solution to the minimum.

This function is called in `Alpha()` to minimize the mean square differences between the theoretical autocorrelation function of an AR1 and the first guess of estimated autocorrelation function `estacf`, using only the first two lags.

## Usage

```
FitAcfCoef(a, b)
```

## Arguments

|                |                                                                  |
|----------------|------------------------------------------------------------------|
| <code>a</code> | Coefficient $a$ : first estimate of the autocorrelation at lag 1 |
| <code>b</code> | Coefficient $b$ : first estimate of the autocorrelation at lag 2 |

## Value

Best estimate of the autocorrelation at lag 1

## Author(s)

History:

0.1 - 2012-06 (L. Auger, <ludovic.auger@meteo.fr>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
series <- GenSeries(1000, 0.35, 2, 1)
estacf <- acf(series[951:1000], plot = FALSE)$acf
alpha <- FitAcfCoef(max(estacf[2], 0), max(estacf[3], 0))
print(alpha)
```

FitAutocor

*Fits an AR1 Autocorrelation Function Using Dichotomy***Description**

This function fits the theoretical autocorrelation function of an AR1 to the first guess of estimated autocorrelation function estacf containing any number of lags. The fitting relies on a dichotomial minimisation of the mean square differences between both autocorrelation functions. It returns the autocorrelation at lag 1 of the fitted AR1 process.

**Usage**

```
FitAutocor(estacf, window = c(-1, 1), prec = 0.01)
```

**Arguments**

|        |                                                                              |
|--------|------------------------------------------------------------------------------|
| estacf | First guess of the autocorrelation function                                  |
| window | Interval in which the autocorrelation at lag 1 should be found.              |
| prec   | Precision to which the autocorrelation function at lag 1 is to be estimated. |

**Value**

Best estimate of the autocorrelation at lag 1

**Author(s)**

History:

0.1 - 2012-02 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
series <- GenSeries(1000, 0.35, 2, 1)
estacf <- acf(series[951:1000], plot = FALSE)$acf
alpha <- FitAutocor(estacf, c(-1, 1), 0.01)
print(alpha)
```

---

GenSeries

*Generates An AR1 Time Series*


---

**Description**

This functions generates AR1 processes containing n data, with alpha as autocorrelation at lag 1, and mean and standard deviation provided by the mean and std arguments.

**Usage**

```
GenSeries(n, alpha, mean, std)
```

**Arguments**

|       |                                           |
|-------|-------------------------------------------|
| n     | Length of the timeseries to be generated. |
| alpha | Autocorrelation at lag 1.                 |
| mean  | Mean of the data.                         |
| std   | Standard deviation of the data.           |

**Value**

AR1 timeseries

**Author(s)**

History:

0.1 - 2012-04 (L. Auger, <ludovic.auger@meteo.fr>) - Original code

1.0 - 2012-04 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
series <- GenSeries(1000, 0.35, 2, 1)
plot(series, type = 'l')
```

---

Histo2Hindcast

*Chunks Long Simulations For Comparison With Hindcasts*


---

**Description**

This function reorganizes a long run (historical typically) with only one start date into chunks corresponding to a set of start dates. The expected input structure is the one output from Load() with 4 to 7 dimensions.

**Usage**

```
Histo2Hindcast(varin, sdatesin, sdatesout, nleadtimesout)
```

## Arguments

|                            |                                                                                                                                                                                                  |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>varin</code>         | Input model or observational data:<br><code>c(nmod/nexp/nobs, nmemb/nparam, nsdates, nltimes)</code> up to<br><code>c(nmod/nexp/nobs, nmemb/nparam, nsdates, nltimes, nlevel, nlat, nlon)</code> |
| <code>sdatesin</code>      | Start date of the input matrix 'YYYYMMDD'.                                                                                                                                                       |
| <code>sdatesout</code>     | List of start dates of the output matrix <code>c('YYYYMMDD', 'YYYYMMDD', ...)</code> .                                                                                                           |
| <code>nleadtimesout</code> | Number of leadtimes in the output matrix.                                                                                                                                                        |

## Value

A matrix with the same number of dimensions as the input one, the same dimensions 1 and 2 and potentially the same dimensions 5 to 7. Dimensions 3 and 4 are set by the arguments `sdatesout` and `nleadtimesout`.

## Author(s)

History:

0.1 - 2012-11 (V. Guemas, <vguemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$_$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19901101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
  leadtimemin = 1, leadtimemax = 4, output = 'areave',
  latmin = 27, latmax = 48, lonmin = -12, lonmax = 40,
  configfile = configfile)

## End(Not run)
```

```

start_dates_out <- c('19901101', '19911101', '19921101', '19931101', '19941101')
leadtimes_per_startdate <- 12
experimental_data <- Histo2Hindcast(sampleData$mod, startDates[1],
                                   start_dates_out, leadtimes_per_startdate)
observational_data <- Histo2Hindcast(sampleData$obs, startDates[1],
                                   start_dates_out, leadtimes_per_startdate)
PlotAno(experimental_data, observational_data, start_dates_out,
        toptitle = paste('anomalies reorganized into shorter chunks'),
        ytitle = 'K', fileout='tos_histo2hindcast.eps')

```

---

IniListDims

*Creates A List Of Integer Ranges*


---

## Description

This function generates a list of arrays where those arrays contain integers from 1 to various numbers. This list of arrays is used in the other functions as a list of indices of the elements of the matrices.

## Usage

```
IniListDims(dims, lenlist)
```

## Arguments

|                      |                                                                                                                                                                                                                                                                                                            |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>dims</code>    | The dimensions of a matrix for which we need the possible indices for each dimension. For example, if the dimensions sent are <code>c(3,2,5)</code> , the following list of arrays will be generated:<br><code>list(c(1:3), c(1:2), c(1:5))</code>                                                         |
| <code>lenlist</code> | <code>lenlist</code> is the length of the list because the list will be complemented above <code>length(dims)</code> by arrays of length 1.<br>For example, if <code>lenlist</code> is set to 7, the previous list of arrays will be extended to:<br><code>list(c(1:3), c(1:2), c(1:5), 1, 1, 1, 1)</code> |

## Value

A list with `lenlist` elements, each with arrays with integers from 1 to the numbers in `dims` array and with only 1 for the dimensions above `length(dims)`.

## Author(s)

History:

0.1 - 2011-04 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

## Examples

```

indices <- IniListDims(c(2, 2, 4, 3), 6)
print(indices)

```

---

|           |                                     |
|-----------|-------------------------------------|
| InsertDim | <i>Adds A Dimension To A Matrix</i> |
|-----------|-------------------------------------|

---

**Description**

Add one dimension to the matrix var in position posdim with length lendim and which correspond to lendim repetitions of the var matrix.

**Usage**

```
InsertDim(var, posdim, lendim)
```

**Arguments**

|        |                                              |
|--------|----------------------------------------------|
| var    | Matrix to which a dimension should be added. |
| posdim | Position of the new dimension.               |
| lendim | Length of the new dimension.                 |

**Value**

Matrix with the added dimension.

**Author(s)**

History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

**Examples**

```
a <- array(rnorm(15), dim = c(3, 1, 5, 1))
print(dim(a))
print(dim(a[, , , ]))
print(dim(InsertDim(InsertDim(a[, , , ], 2, 1), 4, 1)))
```

---

|          |                                           |
|----------|-------------------------------------------|
| LeapYear | <i>Checks Whether A Year Is Leap Year</i> |
|----------|-------------------------------------------|

---

**Description**

This function tells whether a year is leap year or not.

**Usage**

```
LeapYear(year)
```

**Arguments**

|      |                                               |
|------|-----------------------------------------------|
| year | The year to tell whether is leap year or not. |
|------|-----------------------------------------------|



**Value**

Boolean telling whether the year is a leap year or not.

**Author(s)**

History:

0.1 - 2011-03 (V. Guemas, <vguemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
print(LeapYear(1990))
print(LeapYear(1991))
print(LeapYear(1992))
print(LeapYear(1993))
```

---

Load

*Loads Experimental And Observational Data*


---

**Description**

This function loads monthly or daily data from a set of specified experimental datasets together with data that date-corresponds from a set of specified observational datasets. See parameters 'storefreq', 'sampleperiod', 'exp' and 'obs'.

Load() arranges the data into two arrays with a similar format with the following dimensions:

1. The number of experimental datasets determined by the user through the argument 'exp' for the experimental data array or the number of observational datasets available for validation for the observational array determined as well by the user through the argument 'obs'.
2. The greatest number of members across all experiments in the experimental data array or across all observational datasets in the observational data array.
3. The number of starting dates determined by the user through the 'sdates' argument (we need to store data of each prediction of the model in each starting date).
4. The greatest number of lead-times.
5. The number of latitudes of the zone we want to consider.
6. The number of longitudes of the zone we want to consider.

Dimensions 5 and 6 are optional and their presence depends on the type of the specified variable (global mean or 2-dimensional) and on the selected output type (area averaged time series, latitude averaged time series, longitude averaged time series or 2-dimensional time series).

In the case of loading an area average the dimensions of the arrays will be only the first 4.

Only a specified variable and a set of starting dates is loaded from each experiment. See parameters 'var' and 'sdates'.

Afterwards, observational data that matches every starting date and lead-time of every experimental dataset is fetched in the file system (so, if two predictions at two different start dates overlap, some observational values will be loaded more than once).

If no data is found in the file system for an experimental or observational array point it is filled with

an NA value.

If the specified output is 2-dimensional or latitude- or longitude-averaged time series all the data is interpolated into a common grid. If the specified output type is area averaged time series the data is averaged on the individual grid of each dataset but can also be averaged after interpolating into a common grid. See parameters 'grid' and 'method'.

Once the two arrays are filled by calling this function, other functions in the s2dverification package that receive as inputs data formatted in this data structure can be executed (e.g: `Clim()` to compute climatologies, `Ano()` to compute anomalies, ...).

`Load()` has many additional parameters to disable values and trim dimensions of selected variable, even masks can be applied to 2-dimensional variables. See parameters 'nmember', 'nmemberobs', 'nleadtime', 'leadtimemin', 'leadtimemax', 'sampleperiod', 'lonmin', 'lonmax', 'latmin', 'latmax', 'maskmod', 'maskobs', 'varmin', 'varmax'.

The parameters 'exp' and 'obs' are lists of dataset identifiers. To fetch the data in the repository associated to each dataset, `Load()` reads a configuration file which associates each pair of (dataset ID, variable name) to a corresponding path pattern in which the dataset and variable data is stored. These patterns can contain wildcards and variables tags that will be replaced automatically by `Load()` with the specified starting dates, member numbers, variable name, etc. Furthermore, each pair can be associated not only to a path but also to other values such as grid type, maximum or minimum allowed values, etc., that make `Load()` capable of loading data stored in multiple formats and naming conventions. See '?ConfigFileOpen' and parameters 'configfile', 'suffixexp' and 'suffixobs' in this help page for more information.

Only NetCDF files are supported. OPeNDAP URLs to NetCDF files are also supported.

All in all, `Load()` can load 2-dimensional or global mean variables in any of the following formats:

- experiments:
  - file per ensemble per starting date (YYYY, MM and DD somewhere in the path)
  - file per member per starting date (YYYY, MM, DD and MemberNumber somewhere in the path, exps with different numbers of members supported)
 (YYYY, MM and DD specify the starting dates of the predictions)
- observations:
  - file per ensemble per month (YYYY and MM somewhere in the path)
  - file per member per month (YYYY, MM and MemberNumber somewhere in the path, obs with different numbers of members supported)
  - file per dataset (No constraints in the path but the time axes in the file have to be properly defined)
 (YYYY and MM correspond to the actual month data in the file)

In all the formats the data can be stored in a daily or monthly frequency, or a multiple of these (see parameters 'storefreq' and 'sampleperiod').

All the data files must contain the target variable with the same name and, that variable, must be defined over time, members, latitude and longitude dimensions in this order, time being the record

dimension, members being only required if in 'file per member per starting date' format, and longitude and latitude being only required if is a two-dimensional variable.

In the case of a two-dimensional variable, the variables longitude and latitude must be defined inside the data file too and must have the same names as the dimension for longitudes and latitudes respectively.

The names of these dimensions (and longitude and latitude variables) can be configured in the configuration file (see ?ConfigFileOpen) via the variables DEFAULT\_DIM\_NAME\_LONGITUDES, DEFAULT\_DIM\_NAME\_LATITUDES and DEFAULT\_DIM\_NAME\_MEMBERS. When generating a new configuration file (see ?ConfigFileCreate) these take as default 'longitude', 'latitude' and 'ensemble'.

All the data files are expected to have numeric values representable with 32 bits. Be aware when choosing the fill values or infinite values in the datasets to load.

The Load() function returns a named list with four components: 'mod', 'obs', 'lat' and 'lon'.

- 'mod' is the array that contains the experimental data.
- 'obs' is the array that contains the observational data.
- 'lat' and 'lon' are the latitudes and longitudes of the grid into which the data is interpolated (0 if the loaded variable is a global mean or the output is an area average).

## Usage

```
Load(var, exp = NULL, obs = NULL, sdates, nmember = NULL, nmemberobs = NULL,
      nleadtime = NULL, leadtimemin = 1, leadtimemax = NULL,
      storefreq = 'monthly', sampleperiod = 1, lonmin = 0, lonmax = 360,
      latmin = -90, latmax = 90, output = 'areave', method = 'conservative',
      grid = NULL, maskmod = vector("list", 15), maskobs = vector("list", 15),
      configfile = NULL, suffixexp = NULL, suffixobs = NULL, varmin = NULL,
      varmax = NULL, silent = FALSE, nprocs = NULL, dimnames = NULL)
```

## Arguments

|     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| var | <p>Name of the variable to load.</p> <p>Must have matching entries in the list of global mean or in the list of 2-dimensional variables in the configuration file.</p> <p>Also must have matching entries together with each dataset specified in 'exp' and 'obs' in any of the experimental dataset tables and in any of the observational dataset tables.</p> <p>This parameter is mandatory.</p> <p>Ex: 'tas'</p>                                                                                                                                                                                                                                                                                      |
| exp | <p>Vector of experimental dataset IDs. Each must have matching entries together with the variable name specified in 'var' in any of the experimental datasets tables in the configuration file.</p> <p>IMPORTANT: Place first the experiment with the largest number of members and, if possible, with the largest number of leadtimes. If not possible, the arguments 'nmember' and/or 'nleadtime' should be filled to not miss any member or leadtime.</p> <p>If 'exp' is not specified or set to NULL, observational data is loaded for each start-date for a period of time as long as the time period between the first specified start date and the current date.</p> <p>Ex: c('ecmwf', 'i00k')</p> |

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| obs         | <p>Vector of observational dataset IDs. Each must have matching entries together with the variable name specified in 'var' in any of the observational datasets tables in the configuration file.</p> <p>IMPORTANT: Place first the observation with the largest number of members. If not possible, the argument 'nmemberobs' should be filled to not miss any member.</p> <p>If 'obs' is not specified or set to NULL, no observational data is loaded.</p> <p>Ex: c('ERSST', 'ERAint')</p>                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| sdates      | <p>Vector of starting dates of the experimental runs to be loaded following the pattern 'YYYYMMDD'.</p> <p>This argument is mandatory.</p> <p>Ex: c('19601101', '19651101', '19701101')</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| nmember     | <p>Vector with the numbers of members to load from the specified experimental datasets in 'exp'.</p> <p>If not specified, the number of members of the first experimental dataset is detected and replied to all the experimental datasets.</p> <p>If a single value is specified it is replied to all the experimental datasets.</p> <p>Data for each member is fetched in the file system. If not found is filled with NA values.</p> <p>An NA value in the 'nmember' list is interpreted as "fetch as many members as the greatest number of members among experimental datasets".</p> <p>Note: It is recommended to specify the number of members of the first experimental dataset if it is stored in file per member format because there are known issues in the automatic detection of members if the path to the dataset in the configuration file contains Shell Globbing wildcards such as '*'.<br/>Ex: c(4, 9)</p>          |
| nmemberobs  | <p>Vector with the numbers of members to load from the specified observational datasets in 'obs'.</p> <p>If not specified, the number of members of the first observational dataset is detected and replied to all the observational datasets.</p> <p>If a single value is specified it is replied to all the observational datasets.</p> <p>Data for each member is fetched in the file system. If not found is filled with NA values.</p> <p>An NA value in the 'nmemberobs' list is interpreted as "fetch as many members as the greatest number of members among observational datasets".</p> <p>Note: It is recommended to specify the number of members of the first observational dataset if it is stored in file per member format because there are known issues in the automatic detection of members if the path to the dataset in the configuration file contains Shell Globbing wildcards such as '*'.<br/>Ex: c(1, 5)</p> |
| nleadtime   | <p>Largest number of lead-times among experimental datasets.</p> <p>Takes by default the number of lead-times of the first experimental dataset in 'exp'.</p> <p>If 'exp' is NULL this argument won't have any effect (see Load() description).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| leadtimemin | <p>Only lead-times higher or equal to 'leadtimemin' are loaded. Takes by default value 1.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| leadtimemax | <p>Only lead-times lower or equal to 'leadtimemax' are loaded. Takes by default the same value as 'nleadtime'.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| storefreq   | <p>Frequency at which the data to be loaded is stored in the file system. Can take values 'monthly' or 'daily'.</p> <p>By default it takes 'monthly'.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Note: Data stored in other frequencies with a period which is divisible by a month can be loaded with a proper use of 'storefreq' and 'sampleperiod' parameters. It can also be loaded if the period is divisible by a day and the observational datasets are stored in a file per dataset format or 'obs' is empty.

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sampleperiod | <p>To load only a subset between 'leadtimemin' and 'leadtimemax' with the period of subsampling 'sampleperiod'.</p> <p>Takes by default value 1 (all lead-times are loaded).</p> <p>See 'storefreq' for more information.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| lonmin       | <p>If a 2-dimensional variable is loaded, values at longitudes lower than 'lonmin' aren't loaded.</p> <p>Must take a value in the range [0, 360] (if negative longitudes are found in the data files these are translated to this range).</p> <p>It is set to 0 if not specified.</p> <p>If 'lonmin' &gt; 'lonmax', data across Greenwich is loaded.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| lonmax       | <p>If a 2-dimensional variable is loaded, values at longitudes higher than 'lonmax' aren't loaded.</p> <p>Must take a value in the range [0, 360] (if negative longitudes are found in the data files these are translated to this range).</p> <p>It is set to 360 if not specified.</p> <p>If 'lonmin' &gt; 'lonmax', data across Greenwich is loaded.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| latmin       | <p>If a 2-dimensional variable is loaded, values at latitudes lower than 'latmin' aren't loaded.</p> <p>Must take a value in the range [-90, 90].</p> <p>It is set to -90 if not specified.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| latmax       | <p>If a 2-dimensional variable is loaded, values at latitudes higher than 'latmax' aren't loaded.</p> <p>Must take a value in the range [-90, 90].</p> <p>It is set to 90 if not specified.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| output       | <p>This parameter determines the format in which the data is arranged in the output arrays.</p> <p>Can take values 'areave', 'lon', 'lat', 'lonlat'.</p> <ul style="list-style-type: none"> <li>• 'areave': Time series of area-averaged variables over the specified domain.</li> <li>• 'lon': Time series of meridional averages as a function of longitudes.</li> <li>• 'lat': Time series of zonal averages as a function of latitudes.</li> <li>• 'lonlat': Time series of 2d fields.</li> </ul> <p>Takes by default the value 'areave'. If the variable specified in 'var' is a global mean, this parameter is forced to 'areave'.</p> <p>All the loaded data is interpolated into the grid of the first experimental dataset except if 'areave' is selected. In that case the area averages are computed on each dataset original grid. A common grid different than the first experiment's can be specified through the parameter 'grid'. If 'grid' is specified when selecting 'areave' output type, all the loaded data is interpolated into the specified grid before calculating the area averages.</p> |
| method       | <p>This parameter determines the interpolation method to be used when regridding data (see 'output'). Can take values 'bilinear', 'bicubic', 'conservative', 'distance-weighted'.</p> <p>Takes by default the value 'conservative'.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| grid       | <p>A common grid can be specified through the parameter 'grid' when loading 2-dimensional data. Data is interpolated into this grid whichever 'output' type is specified. If the selected output type is 'areave' and a 'grid' is specified, the area averages are calculated after interpolating to the specified grid.</p> <p>If not specified and the selected output type is 'lon', 'lat' or 'lonlat', this parameter takes as default value the grid of the first experimental dataset, which is read from the configuration file.</p> <p>The grid must be supported by 'cdo' tools: rNXxNY or tTRgrid.</p> <p>Ex: 'r96x72'</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| maskmod    | <p>List of masks to be applied to the data of each experimental dataset respectively, if a 2-dimensional variable is specified in 'var'. Each mask is a matrix with dimensions c(longitudes, latitudes) with the same size as the common grid or with the same size of the grid of the corresponding experimental dataset if 'areave' output type is specified and no common 'grid' is specified. A value of 1 at a point of the mask keeps the original value at that point whereas a value of 0 disables it (replaces by an NA value).</p> <p>By default all values are kept (all ones).</p> <p>If you are loading maps (i.e. 'lonlat', 'lon' or 'lat' output types) all the data will be interpolated onto the common 'grid'. If you want to specify a mask, you will have to provide it already interpolated onto the common grid (you may use 'cdo' for this purpose). It is not usual to apply different masks on experimental datasets on the same grid, so all the experiment masks are expected to be the same. When loading maps, any masks defined for the observational data will be ignored to make sure the same mask is applied to the experimental and observational data. Warning: list() compulsory even if loading 1 experimental dataset only!</p> <p>Ex: list(array(1, dim = c(num_lons, num_lats)))</p> |
| maskobs    | <p>List of masks to be applied to the data of each observational dataset respectively, if a 2-dimensional variable is specified in 'var'. Each mask is a matrix with dimensions c(longitudes, latitudes) with the same size as the common grid or with the same size of the associated observational dataset if 'areave' output type is specified and no common 'grid' is specified. A value of 1 at a point of the mask keeps the original value at that point whereas a value of 0 disables it (replaces by an NA value).</p> <p>By default all values are kept (all ones).</p> <p>If you are loading maps (i.e. 'lonlat', 'lon' or 'lat' output types) all the data will be interpolated onto the common 'grid'. If you want to specify a mask, you will have to provide it already interpolated onto the common grid (you may use 'cdo' for this purpose). It is not usual to apply different masks on experimental datasets on the same grid, so all the experiment masks are expected to be the same. When loading maps, any masks defined for the observational data will be ignored to make sure the same mask is applied to the experimental and observational data. Warning: list() compulsory even if loading 1 observational dataset only!</p> <p>Ex: list(array(1, dim = c(num_lons, num_lats)))</p>             |
| configfile | <p>Path to the s2dverification configuration file from which information on location in file system (and other) of datasets is retrieved.</p> <p>By default the configuration file used at IC3 is used (it is included in the package).</p> <p>Check the IC3's configuration file or a template of configuration file in the folder 'inst/config' in the package.</p> <p>Check further information on the configuration file mechanism in '?LoadCon-</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | figurationFile'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| suffixexp | <p>Vector of suffixes used to build the dataset path of the experimental datasets respectively. Some times paths to datasets can vary depending on slight differences in model adjustments, which leads to an addition of a suffix in the common path pattern for the rest of experimental datasets. In such situation 'suffixexp' can help.</p> <p>Each pair of experimental dataset ID and variable name can have a suffix associated in the configuration file.</p> <p>If only one suffix is specified all experimental datasets will take the same suffix. An NA value in the list of suffixes is interpreted as "take the suffix specified in the configuration file".</p> <p>Ex: c('_f6h', '_3hourly')</p>                                                                                         |
| suffixobs | <p>Vector of suffixes used to build the dataset path of the observational datasets respectively. Some times paths to datasets can vary depending on slight differences in postprocessings or reanalises adjustments, which leads to an addition of a suffix in the common path pattern for the rest of observational datasets. In such situation 'suffixobs' can help.</p> <p>Each pair of observational dataset ID and variable name can have a suffix associated in the configuration file.</p> <p>If only one suffix is specified all observational datasets will take the same suffix. An NA value in the list of suffixes is interpreted as "take the suffix specified in the configuration file".</p> <p>Ex: c('_f6h', '_3hourly')</p>                                                             |
| varmin    | <p>Loaded experimental and observational data values smaller than 'varmin' will be disabled (replaced by NA values).</p> <p>Takes by default the value specified in the configuration file.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| varmax    | <p>Loaded experimental and observational data values greater than 'varmax' will be disabled (replaced by NA values).</p> <p>Takes by default the value specified in the configuration file.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| silent    | <p>Parameter to show (FALSE) or hide (TRUE) information messages.</p> <p>Warnings will be displayed even if 'silent' is set to TRUE.</p> <p>Takes by default the value 'FALSE'.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| nprocs    | <p>Number of parallel processes created to perform the fetch and computation of data.</p> <p>These processes will use shared memory in the processor in which Load() is launched.</p> <p>By default the number of logical cores in the machine will be detected and as many processes as logical cores there are will be created.</p> <p>A value of 1 won't create parallel processes.</p> <p>When running in multiple processes, if an error occurs in any of the processes, a crash message appears in the R session of the original process but no detail is given about the error. A value of 1 will display all error messages in the original and only R session.</p> <p>Note: the parallel process create other blocking processes each time they need to compute an interpolation via 'cdo'.</p> |
| dimnames  | <p>Named list where the name of each element is a generic name of the expected dimensions inside the NetCDF files. These generic names are 'longitudes', 'latitudes' and 'members'. 'time' is not needed because it's detected automatically by discard.</p> <p>The value associated to each name is the actual dimension name in the NetCDF file.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

The variables in the file that contain the longitudes and latitudes of the data (if the data is a 2-dimensional variable) must have the same name as the longitude and latitude dimensions.

By default, these names are taken from the mandatory variables in the configuration file (DEFAULT\_DIM\_NAME\_LONGITUDE, DEFAULT\_DIM\_NAME\_LATITUDE and DEFAULT\_DIM\_NAME\_MEMBERS). If any of those is defined in the 'dim-names' parameter, it takes priority and overwrites the value in the configuration file. Ex.: list(longitudes = 'x', latitudes = 'y') In that example, the dimension 'members' will take the DEFAULT\_DIM\_NAME\_MEMBERS specified in the configuration file.

## Details

The two output matrices have between 2 and 6 dimensions:

1. Number of experimental/observational datasets.
2. Number of members.
3. Number of startdates.
4. Number of leadtimes.
5. Number of latitudes (optional).
6. Number of longitudes (optional).

but the two matrices have the same number of dimensions and only the first two dimensions can have different lengths depending on the input arguments.

For a detailed explanation of the process, read the documentation attached to the package or check the comments in the code.

## Value

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\$mod</code> | <p>Model outputs.</p> <p>If output = 'areave', matrix with dimensions <code>c(nmod/nexp, nmemb/nparam, nsdates, nltime)</code></p> <p>If output = 'lat', matrix with dimensions <code>c(nmod/nexp, nmemb/nparam, nsdates, nltime, nlat)</code></p> <p>If output = 'lon', matrix with dimensions <code>c(nmod/nexp, nmemb/nparam, nsdates, nltime, nlon)</code></p> <p>If output = 'lonlat', matrix with dimensions <code>c(nmod/nexp, nmemb/nparam, nsdates, nltime, nlat, nlon)</code></p>                   |
| <code>\$obs</code> | <p>Observations. Matrix with same dimensions as '\$mod' except along the first two.</p> <p>If output = 'areave', matrix with dimensions <code>c(nobs, nmemb, nsdates, nltime)</code></p> <p>If output = 'lat', matrix with dimensions <code>c(nobs, nmemb, nsdates, nltime, nlat)</code></p> <p>If output = 'lon', matrix with dimensions <code>c(nobs, nmemb, nsdates, nltime, nlon)</code></p> <p>If output = 'lonlat', matrix with dimensions <code>c(nobs, nmemb, nsdates, nltime, nlat, nlon)</code></p> |



|       |                                                                                                                                                                |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| \$lat | Latitudes of the output grid (default: model grid of the first experiment).<br>If 'areave' is selected or a global mean variable is specified, takes value 0.  |
| \$lon | Longitudes of the output grid (default: model grid of the first experiment).<br>If 'areave' is selected or a global mean variable is specified, takes value 0. |

### Author(s)

#### History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code  
 1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN  
 1.2 - 2015-02 (N. Manubens, <nicolau.manubens at ic3.cat>) - Generalisation + parallelisation  
 1.3 - 2015-07 (N. Manubens, <nicolau.manubens at ic3.cat>) - Improvements related to configuration file mechanism

### Examples

```
# Let's assume we want to perform verification with data of a variable
# called 'tos' from a model called 'model' and observed data coming from
# an observational dataset called 'observation'.
#
# The model was run in the context of an experiment named 'experiment'.
# It simulated from 1st November in 1985, 1990, 1995, 2000 and 2005 for a
# period of 5 years time from each starting date. 5 different sets of
# initial conditions were used so an ensemble of 5 members was generated
# for each starting date.
# The model generated values for the variables 'tos' and 'tas' in a
# 3-hourly frequency but, after some initial post-processing, it was
# averaged over every month.
# The resulting monthly average series were stored in a file for each
# starting date for each variable with the data of the 5 ensemble members.
# The resulting directory tree was the following:
#   model
#   |--> experiment
#       |--> monthly_mean
#           |--> tos_3hourly
#               |   |--> tos_19851101.nc
#               |   |--> tos_19901101.nc
#               |   .
#               |   .
#               |   |--> tos_20051101.nc
#           |--> tas_3hourly
#               |   |--> tas_19851101.nc
#               |   |--> tas_19901101.nc
#               |   .
#               |   .
#               |--> tas_20051101.nc
#
# The observation recorded values of 'tos' and 'tas' at each day of the
# month over that period but was also averaged over months and stored in
# a file per month. The directory tree was the following:
#   observation
#   |--> monthly_mean
#       |--> tos
#           |   |--> tos_198511.nc
```

```

#           |      |--> tos_198512.nc
#           |      |--> tos_198601.nc
#           |      .
#           |      .
#           |      |--> tos_201010.nc
#           |--> tas
#               |--> tas_198511.nc
#               |--> tas_198512.nc
#               |--> tas_198601.nc
#               .
#               .
#               |--> tas_201010.nc
#
# The model data is stored in a file-per-startdate fashion and the
# observational data is stored in a file-per-month, and both are stored in
# a monthly frequency. The file format is NetCDF.
# Hence all the data is supported by Load() (see details and other supported
# conventions in ?Load) but first we need to configure it properly.
#
# These data files are included in the package (in the 'sample_data' folder),
# only for the variable 'tos'. They have been interpolated to a very low
# resolution grid so as to make it on CRAN.
# The original grid names (following CDO conventions) for experimental and
# observational data were 't106grid' and 'r180x89' respectively. The final
# resolutions are 'r20x10' and 'r16x8' respectively.
# The experimental data comes from the decadal climate prediction experiment
# run at IC3 in the context of the CMIP5 project. Its name within IC3 local
# database is 'i00k'.
# The observational dataset used for verification is the 'ERSST'
# observational dataset.
#
# The configuration file 'sample.conf' that we will create in the example
# has the proper entries to load these (see ?LoadConfigFile for details on
# writing a configuration file).
#
# The code is not run because it dispatches system calls to 'cdo' and 'nco'
# which is not allowed as per CRAN policies. You can run it in your system
# though. Instead, the code in 'dontshow' is run, which loads the equivalent
# data already processed in R.
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_$VAR_NAME$_$YEAR$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

```

```
# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
                  output = 'areave', latmin = 27, latmax = 48,
                  lonmin = -12, lonmax = 40, configfile = configfile)

## End(Not run)
```

---

Mean1Dim

*Averages A Matrix Along A Dimension*


---

## Description

Averages the matrix var along the posdim dimension between limits [1] and limits [2] if limits argument is provided by the user.

## Usage

```
Mean1Dim(var, posdim, narm = TRUE, limits = NULL)
```

## Arguments

|        |                                         |
|--------|-----------------------------------------|
| var    | Matrix to average.                      |
| posdim | Dimension to average along.             |
| narm   | Ignore NA (TRUE) values or not (FALSE). |
| limits | Limits to average between.              |

## Value

Matrix with one dimension less than the input one containing the average along posdim dimension.

## Author(s)

History:

0.1 - 2011-04 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

## Examples

```
a <- array(rnorm(24), dim = c(2, 3, 4))
print(a)
print(Mean1Dim(a, 2))
```

---

|             |                                                   |
|-------------|---------------------------------------------------|
| MeanListDim | <i>Averages A Matrix Along Various Dimensions</i> |
|-------------|---------------------------------------------------|

---

**Description**

Averages the matrix var along a set of dimensions given by the argument dims.

**Usage**

```
MeanListDim(var, dims, narm = TRUE)
```

**Arguments**

|      |                                         |
|------|-----------------------------------------|
| var  | Matrix to average.                      |
| dims | List of dimensions to average along.    |
| narm | Ignore NA (TRUE) values or not (FALSE). |

**Value**

Matrix with as many dimensions less than the input matrix as provided by the list dims and containing the average along this list of dimensions.

**Author(s)**

History:

0.1 - 2011-04 (V. Guemas, <vguemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

**Examples**

```
a <- array(rnorm(24), dim = c(2, 3, 4))
print(a)
print(Mean1Dim(a, 2))
print(MeanListDim(a, c(2, 3)))
```

---

|                  |                                                                   |
|------------------|-------------------------------------------------------------------|
| Plot2VarsVsLTime | <i>Plot Two Scores With Confidence Intervals In A Common Plot</i> |
|------------------|-------------------------------------------------------------------|

---

**Description**

Plots two input variables having the same dimensions in a common plot.

One plot for all experiments.

Input variables should have dimensions (nexp/nmod, ntime).

**Usage**

```
Plot2VarsVsLTime(var1, var2, toptitle = "", ytitle = "", monini = 1,
  freq = 12, nticks = NULL, limits = NULL,
  listexp = c("exp1", "exp2", "exp3"),
  listvars = c("var1", "var2"), biglab = FALSE, hlines = NULL,
  leg = TRUE, siglev = FALSE, sizetit = 1,
  fileout = "output_plot2varsvsvertime.eps", show_conf = TRUE)
```

**Arguments**

|                        |                                                                                          |
|------------------------|------------------------------------------------------------------------------------------|
| <code>var1</code>      | Matrix of dimensions (nexp/nmod, ntime).                                                 |
| <code>var2</code>      | Matrix of dimensions (nexp/nmod, ntime).                                                 |
| <code>toptitle</code>  | Main title, optional.                                                                    |
| <code>yttitle</code>   | Title of Y-axis, optional.                                                               |
| <code>monini</code>    | Starting month between 1 and 12. Default = 1.                                            |
| <code>freq</code>      | 1 = yearly, 12 = monthly, 4 = seasonal, ... Default = 12.                                |
| <code>nticks</code>    | Number of ticks and labels on the x-axis, optional.                                      |
| <code>limits</code>    | c(lower limit, upper limit): limits of the Y-axis, optional.                             |
| <code>listexp</code>   | List of experiment names, up to three, optional.                                         |
| <code>listvars</code>  | List of names of input variables, optional.                                              |
| <code>biglab</code>    | TRUE/FALSE for presentation/paper plot. Default = FALSE.                                 |
| <code>hlines</code>    | c(a, b, ...) Add horizontal black lines at Y-positions a, b, ...<br>Default: NULL.       |
| <code>leg</code>       | TRUE/FALSE if legend should be added or not to the plot. Default = TRUE.                 |
| <code>siglev</code>    | TRUE/FALSE if significance level should replace confidence interval.<br>Default = FALSE. |
| <code>sizetit</code>   | Multiplicative factor to change title size, optional.                                    |
| <code>fileout</code>   | Name of output ps file.                                                                  |
| <code>show_conf</code> | TRUE/FALSE to show/not confidence intervals for input variables.                         |

**Details**

Examples of input:

---

RMSE error for a number of experiments and along lead-time: (nexp, ntime)

**Author(s)**

History:

1.0 - 2013-03 (I. Andreu-Burillo, <isabel.andreu-burillo at ic3.cat>) - Original code

**Examples**

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_months, dim_to_smooth)
dim_to_mean <- 2 # Mean along members
required_complete_row <- 3 # Discard start dates that contain NA along lead-times
leadtimes_per_startdate <- 60
rms <- RMS(Mean1Dim(smooth_ano_exp, dim_to_mean),
```

```

Mean1Dim(smooth_ano_obs, dim_to_mean),
compROW = required_complete_row,
limits = c(ceiling((runmean_months + 1) / 2),
           leadtimes_per_startdate - floor(runmean_months / 2)))
smooth_ano_exp_m_sub <- smooth_ano_exp - InsertDim(Mean1Dim(smooth_ano_exp, 2,
                  narm = TRUE), 2, dim(smooth_ano_exp)[2])
spread <- Spread(smooth_ano_exp_m_sub, c(2, 3))
Plot2VarsVsLTime(InsertDim(rms[, , , ], 1, 1), spread$sd,
                 toptitle = 'RMSE and spread', monini = 11, freq = 12,
                 listexp = c('CMIP5 IC3'), listvar = c('RMSE', 'spread'),
                 fileout = 'plot2vars.eps')

```

PlotACC

*Plot Plumes/Timeseries Of Anomaly Correlation Coefficients***Description**

Plots plumes/timeseries of ACC from a matrix with dimensions (output from ACC()):  
 c(nexp, nobs, nsdates, ntime, 4)  
 with the fourth dimension of length 4 containing the lower limit of the 95% confidence interval,  
 the ACC, the upper limit of the 95% confidence interval and the 95% significance level given by a  
 one-sided T-test.

**Usage**

```

PlotACC(ACC, sdates, toptitle = "", sizetit = 1, ytitle = "", limits = NULL,
        legends = NULL, freq = 12, biglab = FALSE, fill = FALSE,
        linezero = FALSE, points = TRUE, vlins = NULL,
        fileout = "output_PlotACC.eps")

```

**Arguments**

|          |                                                                                                                                                                                                                                                                  |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACC      | ACC matrix with with dimensions:<br>c(nexp, nobs, nsdates, ntime, 4)<br>with the fourth dimension of length 4 containing the lower limit of the 95% confidence interval, the ACC, the upper limit of the 95% confidence interval and the 95% significance level. |
| sdates   | List of startdates: c('YYYYMMDD','YYYYMMDD').                                                                                                                                                                                                                    |
| toptitle | Main title, optional.                                                                                                                                                                                                                                            |
| sizetit  | Multiplicative factor to scale title size, optional.                                                                                                                                                                                                             |
| ytitle   | Title of Y-axis for each experiment: c("",""), optional.                                                                                                                                                                                                         |
| limits   | c(lower limit, upper limit): limits of the Y-axis, optional.                                                                                                                                                                                                     |
| legends  | List of flags (characters) to be written in the legend, optional.                                                                                                                                                                                                |
| freq     | 1 = yearly, 12 = monthly, 4 = seasonal, ... Default: 12.                                                                                                                                                                                                         |
| biglab   | TRUE/FALSE for presentation/paper plot, Default = FALSE.                                                                                                                                                                                                         |
| fill     | TRUE/FALSE if filled confidence interval. Default = FALSE.                                                                                                                                                                                                       |
| linezero | TRUE/FALSE if a line at y=0 should be added. Default = FALSE.                                                                                                                                                                                                    |
| points   | TRUE/FALSE if points instead of lines. Default = TRUE.<br>Must be TRUE if only 1 leadtime.                                                                                                                                                                       |
| vlins    | List of x location where to add vertical black lines, optional.                                                                                                                                                                                                  |
| fileout  | Name of the output eps file.                                                                                                                                                                                                                                     |

**Author(s)**

History:

0.1 - 2013-08 (V. Guemas, &lt;virginie.guemas at ic3.cat&gt;) - Original code

1.0 - 2013-09 (N. Manubens, &lt;nicolau.manubens at ic3.cat&gt;) - Formatting to CRAN

**Examples**

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$_$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)
# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
  leadtimemin = 1, leadtimax = 4, output = 'lonlat',
  latmin = 27, latmax = 48, lonmin = -12, lonmax = 40,
  configfile = configfile)

## End(Not run)

sampleData$mod <- Season(sampleData$mod, 4, 11, 12, 2)
sampleData$obs <- Season(sampleData$obs, 4, 11, 12, 2)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
acc <- ACC(Mean1Dim(sampleData$mod, 2),
  Mean1Dim(sampleData$obs, 2))
PlotACC(acc$ACC, startDates, toptitle = "Anomaly Correlation Coefficient")
```

PlotAno

*Plot Raw Or Smoothed Anomalies***Description**

Plots timeseries of raw or smoothed anomalies of any index output from `Load()` or `Ano()` or `Ano_CrossValid()` or `Smoothing()` and organized in matrices with dimensions:

`c(nmod/nexp, nmemb/nparam, nsdates, ntime)` for the model data

`c(nobs, nmemb, nsdates, ntime)` for the observational data





```
smooth_ano_exp <- Smoothing(ano_exp, runmean_nb_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_nb_months, dim_to_smooth)
PlotAno(smooth_ano_exp, smooth_ano_obs, startDates,
        toptitle = paste('smoothed anomalies'), ytitle = c('K', 'K', 'K'),
        legends = 'ERSST', biglab = FALSE, fileout = 'tos_ano.eps')
```

PlotClim

*Plots Climatologies***Description**

Plots climatologies as a function of the forecast time for any index output from `Clim()` and organized in matrix with dimensions:

`c(nmod/nexp, nmemb/nparam, nlttime)` or `c(nmod/nexp, nlttime)` for the experiment data  
`c(nobs, nmemb, nlttime)` or `c(nobs, nlttime)` for the observational data

**Usage**

```
PlotClim(exp_clim, obs_clim = NULL, toptitle = "", ytitle = "", monini = 1,
        freq = 12, limits = NULL, listexp = c("exp1", "exp2", "exp3"),
        listobs = c("obs1", "obs2", "obs3"), biglab = FALSE, leg = TRUE,
        fileout = "output_plotclim.eps", sizetit = 1)
```

**Arguments**

|                       |                                                                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>exp_clim</code> | Matrix containing the experimental data with dimensions:<br><code>c(nmod/nexp, nmemb/nparam, nlttime)</code> or <code>c(nmod/nexp, nlttime)</code> |
| <code>obs_clim</code> | Matrix containing the observational data (optional) with dimensions:<br><code>c(nobs, nmemb, nlttime)</code> or <code>c(nobs, nlttime)</code>      |
| <code>toptitle</code> | Main title, optional                                                                                                                               |
| <code>ytitle</code>   | Title of Y-axis, optional.                                                                                                                         |
| <code>monini</code>   | Starting month between 1 and 12. Default = 1.                                                                                                      |
| <code>freq</code>     | 1 = yearly, 12 = monthly, 4 = seasonal, ... Default = 12.                                                                                          |
| <code>limits</code>   | <code>c(lower limit, upper limit)</code> : limits of the Y-axis, optional.                                                                         |
| <code>listexp</code>  | List of experiment names, optional.                                                                                                                |
| <code>listobs</code>  | List of observational dataset names, optional.                                                                                                     |
| <code>biglab</code>   | TRUE/FALSE for presentation/paper plot. Default = FALSE.                                                                                           |
| <code>leg</code>      | TRUE/FALSE to plot the legend or not.                                                                                                              |
| <code>fileout</code>  | Name of the output eps file.                                                                                                                       |
| <code>sizetit</code>  | Multiplicative factor to scale title size, optional.                                                                                               |

**Author(s)**

History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
PlotClim(clim$clim_exp, clim$clim_obs, toptitle = paste('climatologies'),
         ytitle = 'K', monini = 11, listexp = c('CMIP5 IC3'),
         listobs = c('ERSST'), biglab = FALSE, fileout = 'tos_clim.eps')
```

---

|             |                                                                                |
|-------------|--------------------------------------------------------------------------------|
| PlotEquiMap | <i>Maps A Two-Dimensional Variable On A Cylindrical Equidistant Projection</i> |
|-------------|--------------------------------------------------------------------------------|

---

## Description

Map a two dimensional matrix with (longitude, latitude) dimensions on a cylindrical equidistant latitude and longitude projection.

## Usage

```
PlotEquiMap(var, lon, lat, toptitle = "", sizetit = 1, units = "",
            brks = NULL, cols = NULL, square = TRUE,
            filled.continents = TRUE, contours = NULL, brks2 = NULL,
            dots = NULL, axelab = TRUE, labW = FALSE, intylat = 20, intxlon = 20,
            drawleg = TRUE, boxlim = NULL, boxcol = 'purple2', boxlwd = 10,
            subsampleg = 1, numbfig = 1, colNA = "white")
```

## Arguments

|                   |                                                                                                                                                                                     |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| var               | Matrix to plot with (longitude, latitude) dimensions.                                                                                                                               |
| lon               | Array of longitudes.                                                                                                                                                                |
| lat               | Array of latitudes.                                                                                                                                                                 |
| toptitle          | Title, optional.                                                                                                                                                                    |
| sizetit           | Multiplicative factor to increase title size, optional.                                                                                                                             |
| units             | Units, optional.                                                                                                                                                                    |
| brks              | Colour levels, optional.                                                                                                                                                            |
| cols              | List of colours, optional.                                                                                                                                                          |
| square            | Field coloured with squares (TRUE) for each grid cell or spatial smoothing (FALSE).<br>Default: TRUE.                                                                               |
| filled.continents | Continents filled in grey (TRUE) or represented by a black line (FALSE).<br>Default = TRUE.<br>Filling unavailable if crossing Greenwich.<br>Filling unavailable if square = FALSE. |
| contours          | Matrix to be added to the plot and shown with contours. Default = NULL.                                                                                                             |
| brks2             | Contour levels, optional.                                                                                                                                                           |

|            |                                                                                                                                                                      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| dots       | Matrix with TRUE / FALSE flags to add black dots over the maps (to show where a score is significant for example). Option only available if square = TRUE.           |
| axelab     | TRUE/FALSE, label the axis. Default = TRUE.                                                                                                                          |
| labW       | Label the longitude axis with W instead of minus. Default = FALSE.                                                                                                   |
| intylat    | Interval between latitude ticks on y-axis. Default = 20deg.                                                                                                          |
| intxlon    | Interval between longitude ticks on x-axis. Default = 20deg.                                                                                                         |
| drawleg    | Draw a colorbar. Can be FALSE only if square = FALSE. Must be FALSE if numbfig > 1. Default = TRUE.                                                                  |
| subsampleg | Supersampling factor of the interval between ticks on colorbar. Default = 1 = every colour level.                                                                    |
| numbfig    | Number of figures in the final multipanel.                                                                                                                           |
| colNA      | Color used to represent NA. Default = 'white'                                                                                                                        |
| boxlim     | The area over which to draw a rectangle over the map.<br>A vector of length 4 such that: c(western boundary, southern boundary, eastern boundary, northern boundary) |
| boxcol     | Color of the rectangle. Default: 'purple2'.                                                                                                                          |
| boxlwd     | Thickness of the rectangle side. Default: 10.                                                                                                                        |

### Author(s)

#### History:

0.1 - 2011-11 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

0.2 - 2013-04 (R. Saurral <ramiro.saurral at ic3.cat>) - LabW

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

### Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$mean/$VAR_NAME$_$VAR_NAME$_$YEAR$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
  output = 'lonlat', latmin = 27, latmax = 48, lonmin = -12,
```

```

lonmax = 40, configfile = configfile)

## End(Not run)

PlotEquiMap(sampleData$mod[1, 1, 1, 1, , ], sampleData$lon, sampleData$lat,
             toptitle = 'Predicted sea surface temperature for Nov 1960 from 1st Nov',
             sizetit = 0.5)

```

---

## PlotSection

## *Plots A Vertical Section*

---

### Description

Plot a (longitude,depth) or (latitude,depth) section.

### Usage

```

PlotSection(var, horiz, depth, toptitle = "", sizetit = 1, units = "",
            brks = NULL, cols = NULL, axelab = TRUE, intydep = 200,
            intxhoriz = 20, drawleg = TRUE)

```

### Arguments

|           |                                                                         |
|-----------|-------------------------------------------------------------------------|
| var       | Matrix to plot with (longitude/latitude, depth) dimensions.             |
| horiz     | Array of longitudes or latitudes.                                       |
| depth     | Array of depths.                                                        |
| toptitle  | Title, optional.                                                        |
| sizetit   | Multiplicative factor to increase title size, optional.                 |
| units     | Units, optional.                                                        |
| brks      | Colour levels, optional.                                                |
| cols      | List of colours, optional.                                              |
| axelab    | TRUE/FALSE, label the axis. Default = TRUE.                             |
| intydep   | Interval between depth ticks on y-axis. Default: 200m.                  |
| intxhoriz | Interval between longitude/latitude ticks on x-axis.<br>Default: 20deg. |
| drawleg   | Draw colorbar. Default: TRUE.                                           |

### Author(s)

History:

0.1 - 2012-09 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

### Examples

```

sampleData <- s2dverification::sampleDepthData
PlotSection(sampleData$mod[1, 1, 1, 1, , ], sampleData$lat, sampleData$depth,
            toptitle = 'temperature 1995-11 member 0')

```

---

|               |                                                                            |
|---------------|----------------------------------------------------------------------------|
| PlotStereoMap | <i>Maps A Two-Dimensional Variable On A Polar Stereographic Projection</i> |
|---------------|----------------------------------------------------------------------------|

---

### Description

Map a two dimensional matrix with (longitude, latitude) dimensions on a polar stereographic projection.

### Usage

```
PlotStereoMap(var, lon, lat, latlims = c(60,90), toptitle = "", sizetit = 1,
              units = "", brks = NULL, cols = NULL, filled.continents = FALSE,
              dots = NULL, intlats = 10, drawleg = TRUE, subsampleg = 1,
              colNA = "white")
```

### Arguments

|                   |                                                                                                                    |
|-------------------|--------------------------------------------------------------------------------------------------------------------|
| var               | Matrix to plot with (longitude, latitude) dimensions.                                                              |
| lon               | Array of longitudes.                                                                                               |
| lat               | Array of latitudes.                                                                                                |
| latlims           | Latitudinal limits of the figure.<br>Example : c(60, 90) for the North Pole<br>c(-90,-60) for the South Pole       |
| toptitle          | Title, optional.                                                                                                   |
| sizetit           | Multiplicative factor to increase title size, optional.                                                            |
| units             | Units, optional.                                                                                                   |
| brks              | Colour levels, optional.                                                                                           |
| cols              | List of colours, optional.                                                                                         |
| filled.continents | Continents filled in grey (TRUE) or represented by a black line (FALSE).<br>Default = FALSE.                       |
| dots              | Matrix with TRUE / FALSE flags to add black dots over the maps (to show where a score is significant for example). |
| intlats           | Interval between latitude circles. Default = 10deg.                                                                |
| drawleg           | Draw a colorbar.                                                                                                   |
| subsampleg        | Supersampling factor of the interval between ticks on colorbar.<br>Default = 1 = every colour level.               |
| colNA             | Color used to represent NA. Default = 'white'                                                                      |

### Author(s)

History:

1.0 - 2014-07 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

## Description

Plots The Correlation (`Corr()`) or the Root Mean Square Error (`RMS()`) between the forecasted values and their observational counterpart or the slopes of their trends (`Trend()`) or the InterQuartile Range, Maximum-Minimum, Standard Deviation or Median Absolute Deviation of the Ensemble Members (`Spread()`), or the ratio between the Ensemble Spread and the RMSE of the Ensemble Mean (`RatioSDRMS()`) along the forecast time for all the input experiments on the same figure with their confidence intervals.

## Usage

```
PlotVsLTime(var, toptitle = "", ytitle = "", monini = 1, freq = 12,
            nticks = NULL, limits = NULL, listexp = c("exp1", "exp2", "exp3"),
            listobs = c("obs1", "obs2", "obs3"), biglab = FALSE, hlines = NULL,
            leg = TRUE, siglev = FALSE, fileout = "output_plotvsltime.eps",
            sizetit = 1, show_conf = TRUE)
```

## Arguments

|                        |                                                                                                                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>var</code>       | Matrix containing any Prediction Score with dimensions:<br>( <code>nexp/nmod</code> , 3/4 , <code>nlttime</code> )<br>or ( <code>nexp/nmod</code> , <code>nobs</code> , 3/4 , <code>nlttime</code> ) |
| <code>toptitle</code>  | Main title, optional.                                                                                                                                                                                |
| <code>ytitle</code>    | Title of Y-axis, optional.                                                                                                                                                                           |
| <code>monini</code>    | Starting month between 1 and 12. Default = 1.                                                                                                                                                        |
| <code>freq</code>      | 1 = yearly, 12 = monthly, 4 = seasonal, ... Default = 12.                                                                                                                                            |
| <code>nticks</code>    | Number of ticks and labels on the x-axis, optional.                                                                                                                                                  |
| <code>limits</code>    | <code>c(lower limit, upper limit)</code> : limits of the Y-axis, optional.                                                                                                                           |
| <code>listexp</code>   | List of experiment names, optional.                                                                                                                                                                  |
| <code>listobs</code>   | List of observation names, optional.                                                                                                                                                                 |
| <code>biglab</code>    | TRUE/FALSE for presentation/paper plot. Default = FALSE.                                                                                                                                             |
| <code>hlines</code>    | <code>c(a,b, ...)</code> Add horizontal black lines at Y-positions a,b, ...<br>Default = NULL.                                                                                                       |
| <code>leg</code>       | TRUE/FALSE if legend should be added or not to the plot. Default = TRUE.                                                                                                                             |
| <code>siglev</code>    | TRUE/FALSE if significance level should replace confidence interval.<br>Default = FALSE.                                                                                                             |
| <code>fileout</code>   | Name of the output eps file.                                                                                                                                                                         |
| <code>sizetit</code>   | Multiplicative factor to change title size, optional.                                                                                                                                                |
| <code>show_conf</code> | TRUE/FALSE to show/not confidence intervals for input variables.                                                                                                                                     |

## Details

Examples of input:

Model and observed output from `Load()` then `Clim()` then `Ano()` then `Smoothing()`:  
(`nmod`, `nmemb`, `nsdate`, `nltime`) and (`nobs`, `nmemb`, `nsdate`, `nltime`)

then averaged over the members

`Mean1Dim(var_exp/var_obs, posdim = 2):`

(`nmod`, `nsdate`, `nltime`) and (`nobs`, `nsdate`, `nltime`)

then passed through

`Corr(exp, obs, posloop = 1, poscor = 2)` or

`RMS(exp, obs, posloop = 1, posRMS = 2):`

(`nmod`, `nobs`, 3, `nltime`)

would plot the correlations or RMS between each exp & each obs as a function of the forecast time.

## Author(s)

History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

0.2 - 2013-03 (I. Andreu-Burillo, <isabel.andreu-burillo at ic3.cat>) - Introduced parameter `sizetit`

0.3 - 2013-10 (I. Andreu-Burillo, <isabel.andreu-burillo at ic3.cat>) - Introduced parameter `show_conf`

1.0 - 2013-11 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_months, dim_to_smooth)
dim_to_mean <- 2 # Mean along members
required_complete_row <- 3 # Discard startdates for which there are NA leadtimes
leadtimes_per_startdate <- 60
corr <- Corr(Mean1Dim(smooth_ano_exp, dim_to_mean),
             Mean1Dim(smooth_ano_obs, dim_to_mean),
             compROW = required_complete_row,
             limits = c(ceiling((runmean_months + 1) / 2),
                        leadtimes_per_startdate - floor(runmean_months / 2)))
PlotVsLTime(corr, toptitle = "correlations", ytitle = "correlation",
            monini = 11, limits = c(-1, 2), listexp = c('CMIP5 IC3'),
            listobs = c('ERSST'), biglab = FALSE, hlines = c(-1, 0, 1),
            fileout = 'tos_cor.eps')
```

## Description

Compute probabilistic bins of a forecast year (fcyr) relative to the forecast climatology over the whole period of anomalies excluding the selected forecast year (fcyr).

## Usage

```
ProbBins(ano, fcyr, thr, quantile=TRUE, posdates=3, posdim=2,
         compPeriod = "Full period")
```

## Arguments

|            |                                                                                                                                                                                                 |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ano        | Array of anomalies from Ano.<br>Must be of dimension (nexp, nmemb, nsdates, nleadtime, nlon, nlat)                                                                                              |
| fcyr       | Number of the forecast year of the anomalies.                                                                                                                                                   |
| thr        | values used to bin the anomalies.                                                                                                                                                               |
| quantile   | If quantile=TRUE (default), the threshold (thr) are quantiles.<br>If quantile=FALSE the threshold (thr) introduced are the specified thresholds.                                                |
| posdates   | Position of the associated dimension with the start dates (default=3).                                                                                                                          |
| posdim     | Position of the dimension which will be combined with posdates to compute the quantiles (default=2).                                                                                            |
| compPeriod | Three options: "Full period"/"Without fcyr"/"cross-validation" (The probabilities are computed with the terciles based on ano/ano with the removed fcyr/cross-validation)(default=Full period). |

## Value

Matrix with probabilistic information and dimensions:  
c(length(thr+1), nfcyr, nmemb/nparam, nmod/nexp/nobs, nfcyr, ntime, nlat, nlon)

## Author(s)

History:  
1.0 - 2013 (F.Lienert) - Original code  
2.0 - 2014-03 (N. Gonzalez and V.Torralba, <veronica.torralba at ic3.cat>) - debugging

## Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
                   dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
```



```

    file_path = '$STORE_FREQ$mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
    dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
    file_path = '$STORE_FREQ$mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
    output = 'lonlat', latmin = 27, latmax = 48, lonmin = -12,
    lonmax = 40, configfile = configfile)

## End(Not run)

clim <- Clim(sampleMap$mod, sampleMap$obs)
ano_exp <- Ano(sampleMap$mod, clim$clim_exp)
PB <- ProbBins(ano_exp, fcyr = 3, thr = c(1/3, 2/3), quantile = TRUE, posdates = 3,
    posdim = 2)

```

RatioRMS

*Computes The Ratio Between The RMSE Scores of 2 Experiments.***Description**

Matrix `var_exp1` / `var_exp2` / `var_obs` should have the same dimensions.  
The ratio  $\text{RMSE}(\text{var\_exp1}, \text{var\_obs}) / \text{RMSE}(\text{var\_exp2}, \text{var\_obs})$  is output.  
The p-value is provided by a two-sided Fischer test.

**Usage**

```
RatioRMS(var_exp1, var_exp2, var_obs, posRMS = 1)
```

**Arguments**

|                       |                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------|
| <code>var_exp1</code> | Matrix of experimental data 1.                                                       |
| <code>var_exp2</code> | Matrix of experimental data 2, same dimensions as <code>var_exp1</code> .            |
| <code>var_obs</code>  | Matrix of observational data, same dimensions as <code>var_exp1</code> .             |
| <code>posRMS</code>   | Dimension along which the RMSE are to be computed = the position of the start dates. |

**Value**

Matrix with the same dimensions as `var_exp1`/`var_exp2`/`var_obs` except along `posRMS` where the dimension has length 2.  
The dimension 2 corresponds to the ratio between the RMSE ( $\text{RMSE1}/\text{RMSE2}$ ) and the p.value of the two-sided Fisher test with  $H_0: \text{RMSE1}/\text{RMSE2} = 1$ .

**Author(s)**

History:

0.1 - 2011-11 (V. Guemas, <vguemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

## Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$_mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
  output = 'lonlat', latmin = 27, latmax = 48, lonmin = -12,
  lonmax = 40, configfile = configfile)

## End(Not run)

leadtimes_dimension <- 4
initial_month <- 11
mean_start_month <- 12
mean_stop_month <- 2
sampleData$mod <- Season(sampleData$mod, leadtimes_dimension, initial_month,
  mean_start_month, mean_stop_month)
sampleData$obs <- Season(sampleData$obs, leadtimes_dimension, initial_month,
  mean_start_month, mean_stop_month)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
rrms <- RatioRMS(Mean1Dim(ano_exp[, 1:2, , , ], 1)[, 1, , ],
  ano_exp[, 3, , , ][, 1, , ],
  Mean1Dim(ano_obs, 2)[1, , 1, , ], 1)
PlotEquiMap(rrms[1, , ], sampleData$lon, sampleData$lat,
  toptitle = 'Ratio RMSE')
```

---

RatioSDRMS

---

*Computes The Ratio Between the Ensemble Spread and the RMSE of the Ensemble Mean*


---

## Description

Matrices var\_exp & var\_obs should have dimensions between  
c(nmod/nexp, nmemb/nparam, nsdates, ntime)

and

`c(nmod/nexp, nmemb/nparam, nsdates, nlttime, nlevel, nlat, nlon)`

The ratio between the standard deviation of the members around the ensemble mean in `var_exp` and the RMSE between `var_exp` and `var_obs` is output for each experiment and each observational dataset.

The p-value is provided by a one-sided Fischer test.

## Usage

```
RatioSDRMS(var_exp, var_obs)
```

## Arguments

|                      |                                                                                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>var_exp</code> | Model data:<br><code>c(nmod/nexp, nmemb/nparam, nsdates, nlttime)</code> up to<br><code>c(nmod/nexp, nmemb/nparam, nsdates, nlttime, nlevel, nlat, nlon)</code> |
| <code>var_obs</code> | Observational data:<br><code>c(nobs, nmemb, nsdates, nlttime)</code> up to<br><code>c(nobs, nmemb, nsdates, nlttime, nlevel, nlat, nlon)</code>                 |

## Value

Matrix with dimensions `c(nexp/nmod, nobs, 2, nlttime)` up to `c(nexp/nmod, nobs, 2, nlttime, nlevel, nlat, nlon)` dimensions. The dimension 2 corresponds to the ratio (SD/RMSE) and the p.value of the one-sided Fisher test with  $H_0: SD/RMSE = 1$ .

## Author(s)

History:

0.1 - 2011-12 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau-manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# Load sample data as in Load() example:
example(Load)
rsdrms <- RatioSDRMS(sampleData$mod, sampleData$obs)
rsdrms2 <- array(dim = c(dim(rsdrms)[1:2], 4, dim(rsdrms)[4]))
rsdrms2[, , 2, ] <- rsdrms[, , 1, ]
rsdrms2[, , 4, ] <- rsdrms[, , 2, ]
PlotVsLTime(rsdrms2, toptitle = "Ratio ensemble spread / RMSE", ytitle = "",
  monini = 11, limits = c(-1, 1.3), listexp = c('CMIP5 IC3'),
  listobs = c('ERSST'), biglab = FALSE, siglev = TRUE,
  fileout = 'tos_rsdrms.eps')
```

## Description

Computes the regression of the input matrix `vary` on the input matrix `varx` along the `posREG` dimension by least square fitting. Provides the slope of the regression, the associated confidence interval, and the intercept.

Provides also the `vary` data filtered out from the regression onto `varx`.

The confidence interval relies on a student-T distribution.

## Usage

```
Regression(vary, varx, posREG = 2)
```

## Arguments

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| <code>vary</code>   | Matrix of any number of dimensions up to 10.                                        |
| <code>varx</code>   | Matrix of any number of dimensions up to 10. Same dimensions as <code>vary</code> . |
| <code>posREG</code> | Position along which to compute the regression.                                     |

## Value

|                           |                                                                                                                                                                                                                                                                                                            |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\$regression</code> | Matrix with same dimensions as <code>varx</code> and <code>vary</code> except along <code>posREG</code> dimension which is replaced by a length 4 dimension, corresponding to the lower limit of the 95% confidence interval, the slope, the upper limit of the 95% confidence interval and the intercept. |
| <code>\$filtered</code>   | Same dimensions as <code>vary</code> filtered out from the regression onto <code>varx</code> along the <code>posREG</code> dimension.                                                                                                                                                                      |

## Author(s)

History:

0.1 - 2013-05 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# See examples on Load() to understand the first lines in this example
## Not run:
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate',
  dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path,
  file_path = '$STORE_FREQ$mean/$VAR_NAME$_3hourly/$VAR_NAME$_$START_DATE$.nc')
c <- ConfigAddEntry(c, 'observations', 'file-per-month',
  dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path,
  file_path = '$STORE_FREQ$mean/$VAR_NAME$_/$VAR_NAME$_$YEAR$_$MONTH$.nc')
ConfigFileSave(c, configfile, confirm = FALSE)
```

```
# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
                  output = 'lonlat', latmin = 27, latmax = 48, lonmin = -12,
                  lonmax = 40, configfile = configfile)

## End(Not run)

sampleData$mod <- Season(sampleData$mod, 4, 11, 12, 2)
sampleData$obs <- Season(sampleData$obs, 4, 11, 12, 2)
reg <- Regression(Mean1Dim(sampleData$mod, 2),
                  Mean1Dim(sampleData$obs, 2), 2)
PlotEquiMap(reg$regression[1, 2, 1, , ], sampleData$lon, sampleData$lat,
            toptitle='Regression of the prediction on the observations',
            sizetitle = 0.5)
```

RMS

*Computes Root Mean Square Error Skill Measure***Description**

Matrix `var_exp` & `var_obs` should have the same dimensions except along `posloop` dimension where the length can be different, with the number of experiments/models for `var_exp` (`nexp`) and the number of obserational datasets for `var_obs` (`nobs`).

RMS computes the Root Mean Square Error skill of each `jexp` in `1:nexp` against each jobs in `1:nobs` which gives `nexp` x `nobs` RMSE skill measures for each other grid point of the matrix (each latitude/longitude/level/leadtime).

The RMSE are computed along the `posRMS` dimension which should correspond to the `startdate` dimension.

If `compROW` is given, the RMSE are computed only if rows along the `compROW` dimension are complete between `limits[1]` and `limits[2]`, that mean with no NA between `limits[1]` and `limits[2]`. This option can be activated if the user wishes to account only for the forecasts for which observations are available at all leadtimes.

Default: `limits[1] = 1` and `limits[2] = length(compROW dimension)`.

The confidence interval relies on a `chi2` distribution.

**Usage**

```
RMS(var_exp, var_obs, posloop = 1, posRMS = 2, compROW = NULL, limits = NULL)
```

**Arguments**

|                      |                                                                                                                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>var_exp</code> | Matrix of experimental data.                                                                                                                                                                |
| <code>var_obs</code> | Matrix of observational data, same dimensions as <code>var_exp</code> except along <code>posloop</code> dimension, where the length can be <code>nobs</code> instead of <code>nexp</code> . |
| <code>posloop</code> | Dimension <code>nobs</code> and <code>nexp</code> .                                                                                                                                         |
| <code>posRMS</code>  | Dimension along which RMSE are to be computed (the dimension of the start dates).                                                                                                           |
| <code>compROW</code> | Data taken into account only if ( <code>compROW</code> )th row is complete.<br>Default = NULL.                                                                                              |
| <code>limits</code>  | Complete between <code>limits[1]</code> & <code>limits[2]</code> . Default = NULL.                                                                                                          |

**Value**

Matrix with dimensions:

`c(length(posloop) in var_exp, length(posloop) in var_obs, 3, all other dimensions of var_exp & var_obs except posRMS).`

The dimension 3 corresponds to the lower limit of the 95% confidence interval, the RMSE and the upper limit of the 95% confidence interval.

**Author(s)**

History:

0.1 - 2011-05 (V. Guemas, <vguemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_months, dim_to_smooth)
dim_to_mean <- 2 # Mean along members
required_complete_row <- 3 # Discard start-dates for which some leadtimes are missing
leadtimes_per_startdate <- 60
rms <- RMS(Mean1Dim(smooth_ano_exp, dim_to_mean),
           Mean1Dim(smooth_ano_obs, dim_to_mean),
           compROW = required_complete_row,
           limits = c(ceiling((runmean_months + 1) / 2),
                      leadtimes_per_startdate - floor(runmean_months / 2)))
PlotVsLTime(rms, toptitle = "Root Mean Square Error", ytitle = "K",
            monini = 11, limits = NULL, listexp = c('CMIP5 IC3'),
            listobs = c('ERSST'), biglab = FALSE, hlines = c(0),
            fileout = 'tos_rms.eps')
```

---

RMSSS

---

*Computes Root Mean Square Skill Score*


---

**Description**

Arrays `var_exp` & `var_obs` should have the same dimensions except along `posloop` where the length can be different, with the number of experiments/models for `var_exp` (`nexp`) and the number of observational datasets for `var_obs` (`nobs`).

RMSSS computes the Root Mean Square Skill Score of each `jexp` in `1:nexp` against each jobs in `1:nobs` which gives `nexp x nobs` RMSSS for each other grid point of the matrix (each latitude/longitude/level/leadtime).

The RMSSS are computed along the `posRMS` dimension which should correspond to the `startdate` dimension.

The p-value is provided by a one-sided Fisher test.

**Usage**

```
RMSSS(var_exp, var_obs, posloop = 1, posRMS = 2)
```

**Arguments**

|         |                                                                                                                                       |
|---------|---------------------------------------------------------------------------------------------------------------------------------------|
| var_exp | Array of experimental data.                                                                                                           |
| var_obs | Array of observational data, same dimensions as var_exp except along posloop dimension, where the length can be nobs instead of nexp. |
| posloop | Dimension nobs and nexp.                                                                                                              |
| posRMS  | Dimension along which the RMSE are to be computed (the dimension of the start dates).                                                 |

**Value**

Array with dimensions :  
 c(length(posloop) in var\_exp, length(posloop) in var\_obs, 2, all other dimensions of var\_exp & var\_obs except posRMS).  
 The dimension 2 corresponds to the RMSSS and the p.value of the one-sided Fisher test with  $H_0$ : RMSSS = 0.

**Author(s)**

History:  
 0.1 - 2012-04 (V. Guemas, <vguemas at ic3.cat>) - Original code  
 1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
rmsss <- RMSSS(Mean1Dim(ano_exp, 2), Mean1Dim(ano_obs, 2))
rmsss2 <- array(dim = c(dim(rmsss)[1:2], 4, dim(rmsss)[4]))
rmsss2[, , 2, ] <- rmsss[, , 1, ]
rmsss2[, , 4, ] <- rmsss[, , 2, ]
PlotVsLTime(rmsss, toptitle = "Root Mean Square Skill Score", ytitle = "",
             monini = 11, limits = c(-1, 1.3), listexp = c('CMIP5 IC3'),
             listobs = c('ERSST'), biglab = FALSE, hlines = c(-1, 0, 1),
             fileout = 'tos_rmsss.eps')
```

sampleDepthData

*Sample of Experimental Data for Forecast Verification In Function Of  
Latitudes And Depths*

**Description**

This data set provides data in function of latitudes and depths for the variable 'tos', i.e. sea surface temperature, from the decadal climate prediction experiment run at IC3 in the context of the CMIP5 project.

Its name within IC3 local database is 'i00k'.

**Usage**

```
data(sampleDepthData)
```

**Format**

The data set provides with a variable named 'sampleDepthData'.

sampleDepthData\$exp is an array that contains the experimental data and the dimension meanings and values are:

```
c(# of experimental datasets, # of members, # of starting dates, # of lead-times, # of depths, # of latitudes)
c(1, 5, 3, 60, 7, 21)
```

sampleDepthData\$obs should be an array that contained the observational data but in this sample is not defined (NULL).

sampleDepthData\$depths is an array with the 7 longitudes covered by the data.

sampleDepthData\$lat is an array with the 21 latitudes covered by the data.

---

sampleMap

*Sample Of Observational And Experimental Data For Forecast Verification In Function Of Longitudes And Latitudes*

---

**Description**

This data set provides data in function of longitudes and latitudes for the variable 'tos', i.e. sea surface temperature, over the mediterranean zone from the sample experimental and observational datasets attached to the package. See examples on how to use Load() for details.

The data is provided through a variable named 'sampleMap' and is structured as expected from the 'Load()' function in the 's2dverification' package if was called as follows:

```
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAMES$')
```



```

obs_data_path <- paste0(data_path, '/$OBS_NAMES$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate', dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path, file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$ST')
c <- ConfigAddEntry(c, 'observations', 'file-per-month', dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path, file_path = '$STORE_FREQ$_mean/$VAR_NAME/$VAR_NAME$_$YEAR$MO')
ConfigFileSave(c, configfile, confirm = FALSE)

```

```

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
output = 'lonlat', latmin = 27, latmax = 48, lonmin = -12,
lonmax = 40, configfile = configfile)

```

Check the documentation on 'Load()' in the package 's2dverification' for more information.

## Usage

```
data(sampleMap)
```

## Format

The data set provides with a variable named 'sampleMap'.

sampleMap\$mod is an array that contains the experimental data and the dimension meanings and values are:

```

c(# of experimental datasets, # of members, # of starting dates, # of lead-times, # of latitudes, # of longitudes)
c(1, 3, 5, 60, 2, 3)

```

sampleMap\$obs is an array that contains the observational data and the dimension meanings and values are:

```

c(# of observational datasets, # of members, # of starting dates, # of lead-times, # of latitudes, # of longitudes)
c(1, 1, 5, 60, 2, 3)

```

sampleMap\$lat is an array with the 2 latitudes covered by the data (see examples on Load() for details on why such low resolution).

sampleMap\$lon is an array with the 3 longitudes covered by the data (see examples on Load() for details on why such low resolution).

---

|                  |                                                                                                 |
|------------------|-------------------------------------------------------------------------------------------------|
| sampleTimeSeries | <i>Sample Of Observational And Experimental Data For Forecast Verification As Area Averages</i> |
|------------------|-------------------------------------------------------------------------------------------------|

---

## Description

This data set provides area averaged data for the variable 'tos', i.e. sea surface temperature, over the mediterranean zone from the example datasets attached to the package. See examples on Load() for more details.

The data is provided through a variable named 'sampleTimeSeries' and is structured as expected from the 'Load()' function in the 's2dverification' package if was called as follows:

```
configfile <- paste0(tempdir(), '/sample.conf')
ConfigFileCreate(configfile, confirm = FALSE)
c <- ConfigFileOpen(configfile)
c <- ConfigEditDefinition(c, 'DEFAULT_GRID', 'r20x10', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MIN', '-1e19', confirm = FALSE)
c <- ConfigEditDefinition(c, 'DEFAULT_VAR_MAX', '1e19', confirm = FALSE)
c <- ConfigAddVar(c, '2d', 'tos')
data_path <- system.file('sample_data', package = 's2dverification')
exp_data_path <- paste0(data_path, '/model/$EXP_NAME$')
obs_data_path <- paste0(data_path, '/$OBS_NAME$')
c <- ConfigAddEntry(c, 'experiments', 'file-per-startdate', dataset_name = 'experiment', var_name = 'tos', main_path = exp_data_path, file_path = '$STORE_FREQ$_mean/$VAR_NAME$_3hourly/$VAR_NAME$_$STARTDATE$')
c <- ConfigAddEntry(c, 'observations', 'file-per-month', dataset_name = 'observation', var_name = 'tos', main_path = obs_data_path, file_path = '$STORE_FREQ$_mean/$VAR_NAME$_$VAR_NAME$_$YEAR$MONTH$')
ConfigFileSave(c, configfile, confirm = FALSE)

# Now we are ready to use Load().
startDates <- c('19851101', '19901101', '19951101', '20001101', '20051101')
sampleData <- Load('tos', c('experiment'), c('observation'), startDates,
output = 'areave', latmin = 27, latmax = 48, lonmin = -12,
lonmax = 40, configfile = configfile)
```

Check the documentation on 'Load()' in the package 's2dverification' for more information.

## Usage

```
data(sampleTimeSeries)
```

## Format

The data set provides with a variable named 'sampleTimeSeries'.

sampleTimeSeries\$mod is an array that contains the experimental data and the dimension meanings and values are:

`c`(# of experimental datasets, # of members, # of starting dates, # of lead-times)  
`c`(1, 3, 5, 60)

`sampleTimeSeries$obs` is an array that contains the observational data and the dimension meanings and values are:

`c`(# of observational datasets, # of members, # of starting dates, # of lead-times)  
`c`(1, 1, 5, 60)

`sampleTimeSeries$lat` is an array with the 2 latitudes covered by the data that was area averaged to calculate the time series (see examples on `Load()` for details on why such low resolution).

`sampleTimeSeries$lon` is an array with the 3 longitudes covered by the data that was area averaged to calculate the time series (see examples on `Load()` for details on why such low resolution).

---

|        |                                |
|--------|--------------------------------|
| Season | <i>Computes Seasonal Means</i> |
|--------|--------------------------------|

---

## Description

Computes seasonal means on timeseries organized in a matrix of any number of dimensions up to 10 dimensions where the time dimension is one of those 10 dimensions.

## Usage

```
Season(var, posdim = 4, monini, moninf, monsup)
```

## Arguments

|                     |                                                                  |
|---------------------|------------------------------------------------------------------|
| <code>var</code>    | Matrix containing the timeseries along one of its dimensions.    |
| <code>posdim</code> | Dimension along which to compute seasonal means = Time dimension |
| <code>monini</code> | First month of the time-series: 1 to 12.                         |
| <code>moninf</code> | Month when to start the seasonal means: 1 to 12.                 |
| <code>monsup</code> | Month when to stop the seasonal means: 1 to 12.                  |

## Value

Matrix with the same dimensions as `var` except along the `posdim` dimension which length corresponds to the number of seasons. Partial seasons are not accounted for.

## Author(s)

History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)
leadtimes_dimension <- 4
initial_month <- 11
mean_start_month <- 12
mean_stop_month <- 2
season_means_mod <- Season(sampleData$mod, leadtimes_dimension, initial_month,
                           mean_start_month, mean_stop_month)
season_means_obs <- Season(sampleData$obs, leadtimes_dimension, initial_month,
                           mean_start_month, mean_stop_month)
PlotAno(season_means_mod, season_means_obs, startDates,
         toptitle = paste('winter (DJF) temperatures'), ytitle = c('K'),
         legends = 'ERSST', biglab = FALSE, fileout = 'tos_season_means.eps')
```

---

SelIndices

---

*Slices A Matrix Along A Dimension*


---

**Description**

This function allows to select a subensemble from a matrix of any dimensions, providing the dimension along which the user aims at cutting the input matrix and between which indices.

**Usage**

```
SelIndices(var, posdim, limits)
```

**Arguments**

|        |                                                                         |
|--------|-------------------------------------------------------------------------|
| var    | A matrix of any dimensions.                                             |
| posdim | The dimension along which a submatrix should be selected.               |
| limits | The lower and upper indice of the selection along the posdim dimension. |

**Value**

The sliced matrix.

**Author(s)**

History:

0.1 - 2011-04 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
a <- array(rnorm(24), dim = c(2, 3, 4, 1))
print(a)
print(a[, , 2:3, ])
print(dim(a[, , 2:3, ]))
print(SelIndices(a, 3, c(2, 3)))
print(dim(SelIndices(a, 3, c(2, 3))))
```

---

Smoothing

*Smoothes A Matrix Along A Dimension*


---

**Description**

Smoothes a matrix of any number of dimensions up to 10 dimensions along one of its dimensions

**Usage**

```
Smoothing(var, runmeanlen = 12, numdimt = 4)
```

**Arguments**

|            |                                                                                                                                                                                                                |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| var        | «««< HEAD Array to be smoothed along one of its dimension (typically the forecast time dimension). ===== Matrix to be smoothed along one of its dimension (typically the forecast time dimension). »»»> master |
| runmeanlen | Running mean length in number of sampling units (typically months).                                                                                                                                            |
| numdimt    | Dimension to smooth.                                                                                                                                                                                           |

**Value**

Array with same the dimensions as 'var' but smoothed along the 'numdimt'-th dimension.

**Author(s)**

History:

0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to R CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
ano_obs <- Ano(sampleData$obs, clim$clim_obs)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_obs <- Smoothing(ano_obs, runmean_months, dim_to_smooth)
PlotAno(smooth_ano_exp, smooth_ano_obs, startDates,
        toptitle = "Smoothed Mediterranean mean SST", ytitle = "K",
        fileout = "tos_smoothed_ano.eps")
```

Spectrum

*Estimates Frequency Spectrum***Description**

This function estimates the frequency spectrum of the `xdata` array together with its 95% and 99% significance level. The output is provided as a matrix with dimensions `c(number of frequencies, 4)`. The column contains the frequency values, the power, the 95% significance level and the 99% one. The spectrum estimation relies on a R built-in function and the significance levels are estimated by a Monte-Carlo method.

**Usage**

```
Spectrum(xdata)
```

**Arguments**

`xdata`                      Array of which the frequency spectrum is required

**Value**

Frequency spectrum with dimensions `c(number of frequencies, 4)`. The column contains the frequency values, the power, the 95% significance level and the 99% one.

**Author(s)**

History:

0.1 - 2012-02 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)

ensmod <- Mean1Dim(sampleData$mod, 2)
for (jstartdate in 1:3) {
  spectrum <- Spectrum(ensmod[1, jstartdate, ])
  for (jlen in 1:dim(spectrum)[1]) {
    if (spectrum[jlen, 2] > spectrum[jlen, 4]) {
      ensmod[1, jstartdate, ] <- Filter(ensmod[1, jstartdate, ],
                                       spectrum[jlen, 1])
    }
  }
}
PlotAno(InsertDim(ensmod, 2, 1), sdates = startDates, fileout =
        'filtered_ensemble_mean.eps')
```

---

|        |                                                                                                                                |
|--------|--------------------------------------------------------------------------------------------------------------------------------|
| Spread | <i>Computes InterQuartile Range, Maximum-Minimum, Standard Deviation and Median Absolute Deviation of the Ensemble Members</i> |
|--------|--------------------------------------------------------------------------------------------------------------------------------|

---

## Description

Computes the InterQuartile Range, the Maximum minus Minimum, the Standard Deviation and the Median Absolute Deviation along the list of dimensions provided by the `posdim` argument (typically along the ensemble member and start date dimension).  
The confidence interval is computed by bootstrapping.

## Usage

```
Spread(var, posdim = 2, narm = TRUE)
```

## Arguments

|                     |                                                                |
|---------------------|----------------------------------------------------------------|
| <code>var</code>    | Matrix of any number of dimensions up to 10.                   |
| <code>posdim</code> | List of dimensions along which to compute IQR/MaxMin/SD/MAD.   |
| <code>narm</code>   | TRUE/FALSE if NA removed/kept for computation. Default = TRUE. |

## Details

Example: ——— To compute IQR, Max-Min, SD & MAD accross the members and start dates of `var` output from `Load()` or `Ano()` or `Ano_CrossValid()`, call:  
`spread(var, posdim = c(2, 3), narm = TRUE)`

## Value

Matrix with the same dimensions as `var` except along the first `posdim` dimension which is replaced by a length 3 dimension, corresponding to the lower limit of the 95% confidence interval, the spread and the upper limit of the 95% confidence interval for each experiment/leadtime/latitude/longitude.

|                       |                            |
|-----------------------|----------------------------|
| <code>\$iqr</code>    | InterQuartile Range.       |
| <code>\$maxmin</code> | Maximum - Minimum.         |
| <code>\$sd</code>     | Standard Deviation.        |
| <code>\$mad</code>    | Median Absolute Deviation. |

## Author(s)

History:  
0.1 - 2011-03 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code  
1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

## Examples

```
# Load sample data as in Load() example:
example(Load)
clim <- Clim(sampleData$mod, sampleData$obs)
ano_exp <- Ano(sampleData$mod, clim$clim_exp)
runmean_months <- 12
dim_to_smooth <- 4 # Smooth along lead-times
smooth_ano_exp <- Smoothing(ano_exp, runmean_months, dim_to_smooth)
smooth_ano_exp_m_sub <- smooth_ano_exp - InsertDim(Mean1Dim(smooth_ano_exp, 2,
  narm = TRUE), 2, dim(smooth_ano_exp)[2])
spread <- Spread(smooth_ano_exp_m_sub, c(2, 3))
PlotVsLTime(spread$iqr,
  toptitle = "Inter-Quartile Range between ensemble members",
  ytitle = "K", monini = 11, limits = NULL,
  listexp = c('CMIP5 IC3'), listobs = c('ERSST'), biglab = FALSE,
  hlines = c(0), fileout = 'tos_iqr.eps')
PlotVsLTime(spread$maxmin, toptitle = "Maximum minus minimum of the members",
  ytitle = "K", monini = 11, limits = NULL,
  listexp = c('CMIP5 IC3'), listobs = c('ERSST'), biglab = FALSE,
  hlines = c(0), fileout = 'tos_maxmin.eps')
PlotVsLTime(spread$sd, toptitle = "Standard deviation of the members",
  ytitle = "K", monini = 11, limits = NULL,
  listexp = c('CMIP5 IC3'), listobs = c('ERSST'), biglab = FALSE,
  hlines = c(0), fileout = 'tos_sd.eps')
PlotVsLTime(spread$mad, toptitle = "Median Absolute Deviation of the members",
  ytitle = "K", monini = 11, limits = NULL,
  listexp = c('CMIP5 IC3'), listobs = c('ERSST'), biglab = FALSE,
  hlines = c(0), fileout = 'tos_mad.eps')
```

---

Trend

---

*Computes Trends*


---

## Description

Computes the trend along the posTR dimension of the matrix var by least square fitting, and the associated an error interval.

Provide also the detrended data.

The confidence interval relies on a student-T distribution.

## Usage

```
Trend(var, posTR = 2, interval = 1)
```

## Arguments

|          |                                                                                                                                                     |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| var      | Matrix of any number of dimensions up to 10.                                                                                                        |
| posTR    | Position along which to compute the trend.                                                                                                          |
| interval | Number of months/years between 2 points along posTR dimension.<br>Default = 1.<br>The trend would be provided in number of units per month or year. |



**Value**

|                          |                                                                                                                                                                                                                                                                                                                      |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\$trend</code>     | Same dimensions as <code>var</code> except along the <code>posTR</code> dimension which is replaced by a length 3 dimension, corresponding to the lower limit of the 95% confidence interval, trends and the upper limit of the 95% confidence interval for each point of the matrix along all the other dimensions. |
| <code>\$detrended</code> | Same dimensions as <code>var</code> with linearly detrended <code>var</code> along the <code>posTR</code> dimension.                                                                                                                                                                                                 |

**Author(s)**

History:

0.1 - 2011-05 (V. Guemas, <virginie.guemas at ic3.cat>) - Original code

1.0 - 2013-09 (N. Manubens, <nicolau.manubens at ic3.cat>) - Formatting to CRAN

**Examples**

```
# Load sample data as in Load() example:
example(Load)
months_between_startdates <- 60
trend <- Trend(sampleData$obs, 3, months_between_startdates)
PlotVsLTime(trend$trend, toptitle = "trend", ytitle = "K / (5 year)",
            monini = 11, limits = c(-1,1), listexp = c('CMIP5 IC3'),
            listobs = c('ERSST'), biglab = FALSE, hlines = 0,
            fileout = 'tos_obs_trend.eps')
PlotAno(trend$detrended, NULL, startDates,
        toptitle = 'detrended anomalies (along the startdates)', ytitle = 'K',
        legends = 'ERSST', biglab = FALSE, fileout = 'tos_detrended_obs.eps')
```

# Index

## \*Topic **datagen**

- .LoadDataFile, 3
- ACC, 6
- Alpha, 8
- Ano, 9
- Ano\_CrossValid, 10
- Clim, 11
- ConfigAddVar, 13
- ConfigApplyMatchingEntries, 14
- ConfigEditDefinition, 16
- ConfigEditEntry, 17
- ConfigFileOpen, 19
- ConfigMatchingVars, 23
- ConfigShowSimilarEntries, 24
- ConfigShowTable, 26
- Consist\_Trend, 27
- Corr, 29
- CRPS, 30
- Enlarge, 31
- Eno, 32
- EnoNew, 33
- Filter, 34
- FitAcfCoef, 35
- FitAutocor, 36
- GenSeries, 37
- Histo2Hindcast, 37
- IniListDims, 39
- InsertDim, 40
- LeapYear, 40
- Load, 41
- Mean1Dim, 51
- MeanListDim, 52
- PlotClim, 57
- ProbBins, 63
- RatioRMS, 65
- RatioSDRMS, 66
- Regression, 67
- RMS, 69
- RMSSS, 70
- s2dverification-package, 3
- Season, 75
- SelIndices, 76

- Smoothing, 77

- Spectrum, 78

- Spread, 79

- Trend, 80

## \*Topic **datasets**

- sampleDepthData, 71

- sampleMap, 72

- sampleTimeSeries, 74

## \*Topic **dplot**

- ColorBar, 12

## \*Topic **dynamic**

- Plot2VarsVsLTime, 52

- PlotACC, 54

- PlotAno, 55

- PlotEquiMap, 58

- PlotSection, 60

- PlotStereoMap, 61

- PlotVsLTime, 62

- s2dverification-package, 3

## \*Topic **package**

- s2dverification-package, 3

- .LoadDataFile, 3

- ACC, 6

- Alpha, 8

- Ano, 9

- Ano\_CrossValid, 10

- Clim, 11

- ColorBar, 12

- ConfigAddEntry (*ConfigEditEntry*), 17

- ConfigAddVar, 13

- ConfigApplyMatchingEntries, 14

- ConfigEditDefinition, 16

- ConfigEditEntry, 17

- ConfigFileCreate (*ConfigFileOpen*), 19

- ConfigFileOpen, 19

- ConfigFileSave (*ConfigFileOpen*), 19

- ConfigMatchingVars, 23

- ConfigRemoveDefinition (*ConfigEditDefinition*), 16

- ConfigRemoveEntry
  - (*ConfigEditEntry*), [17](#)
- ConfigRemoveVar (*ConfigAddVar*), [13](#)
- ConfigShowDefinitions
  - (*ConfigShowTable*), [26](#)
- ConfigShowSimilarEntries, [24](#)
- ConfigShowSimilarVars
  - (*ConfigShowSimilarEntries*), [24](#)
- ConfigShowTable, [26](#)
- ConfigShowVars (*ConfigShowTable*), [26](#)
- Consist\_Trend, [27](#)
- Corr, [29](#)
- CRPS, [30](#)
  
- Enlarge, [31](#)
- Eno, [32](#)
- EnoNew, [33](#)
  
- Filter, [34](#)
- FitAcfCoef, [35](#)
- FitAutocor, [36](#)
  
- GenSeries, [37](#)
  
- Histo2Hindcast, [37](#)
  
- IniListDims, [39](#)
- InsertDim, [40](#)
  
- LeapYear, [40](#)
- Load, [41](#)
  
- Mean1Dim, [51](#)
- MeanListDim, [52](#)
  
- Plot2VarsVsLTime, [52](#)
- PlotACC, [54](#)
- PlotAno, [55](#)
- PlotClim, [57](#)
- PlotEquiMap, [58](#)
- PlotSection, [60](#)
- PlotStereoMap, [61](#)
- PlotVsLTime, [62](#)
- ProbBins, [63](#)
  
- RatioRMS, [65](#)
- RatioSDRMS, [66](#)
- Regression, [67](#)
- RMS, [69](#)
- RMSSS, [70](#)
  
- s2dverification
  - (*s2dverification-package*), [3](#)
- s2dverification-package, [3](#)
- sampleDepthData, [71](#)
- sampleMap, [72](#)
- sampleTimeSeries, [74](#)
- Season, [75](#)
- SelIndices, [76](#)
- Smoothing, [77](#)
- Spectrum, [78](#)
- Spread, [79](#)
  
- Trend, [80](#)